



## DEEP RINGO LED 92733

202 272 811 922 BRG

AVAILABLE IN

**BLACK** 202 272 811 922 B

**BRUSHED ALU** 202 272 811 922 BRA

**BRUSHED ANTHRACITE** 202 272 811 922 BRAT

**BRUSHED BROWN BRONZE** 202 272 811 922 BRBB

**BRUSHED COPPER** 202 272 811 922 BRCU

**BRUSHED GOLD** 202 272 811 922 BRG

**BRUSHED OLD BRONZE** 202 272 811 922 BROB

**CREAM** 202 272 811 922 CR



**FLEMISH BRONZE** 202 272 811 922 FBR

**FLEMISH GOLD** 202 272 811 922 FG

**GOLD COLOURED** 202 272 811 922 GC

**PIANO BLACK** 202 272 811 922 PB

**WHITE** 202 272 811 922 W



[View on website](#)



### General info

|   |  |
|---|--|
| <b>LOCATION</b>                           | indoor   |
| <b>INSTALLATION</b>                       | Ceiling Recessed                                       |
| <b>CUTOUT SHAPE/SIZE (MM)</b>             | round - 76   |
| <b>RECESSED DEPTH (MM)</b>                | 90   |
| <b>THICKNESS OF MOUNTING SURFACE (MM)</b> | min.5  |
| <b>INGRESS PROTECTION</b>                 | IP20   |
| <b>WEIGHT (KG)</b>                        | 0.2  |
| <b>ADJUSTABILITY</b>                      | non adjustable   |
| <b>INFORMATION</b>                        | REFLECTOR FL-33°<br>EXCL.LED POWER SUPPLY 350-500mA-DC |

### Electrical info

|                     |                           |
|---------------------|---------------------------|
| <b>CLASS</b>        | III                       |
| <b>DIM TYPE</b>     | depending on power supply |
| <b>ENERGY CLASS</b> | E                         |
| <b>CERTIFICATES</b> | CB, EAC, ENEC, EPD, LCA   |

### Lightsource info

|                                    |   |
|------------------------------------|---|
| <b>LIGHTSOURCE NAME</b>            | LED   |
| <b>LIGHTSOURCE</b>                 | LED array 5,8-8,6W / CRI>90 (R9: 60) / 2700K / 753-1041lm |
| <b>TM-30 VALUES</b>                | rf: 89 / Rg: 100  |
| <b>SDCM</b>                        | SDCM1   |
| <b>RISKGROUP</b>                   | RG1   |
| <b>LM80</b>                        | L90B10 > 50000  |
| <b>BEAMANGLE</b>                   | 33°   |
| <b>LED TECHNICS (LIGHT SOURCE)</b> | 1041lm // 8,6W // 121lm/W                                 |
| <b>LED TECHNICS (LUMINAIRE)</b>    | 768lm // 9,9W // 78lm/W                                   |

### Requirements

LED POWER SUPPLY 350 / 500mA-DC DIM

# DELTALIGHT

## DEEP RINGO LED 92733

202 272 811 922 BRG

For detailed installation instructions, please consult the manual : [202\\_272\\_811\\_XXX\\_HAND.pdf](#)

### CEILING COMPATIBILITY

| Ceiling Type  | Mounting Kit |
|---|--------------|
|  System ceiling               | -            |
|  Plasterboard                 | -            |
|  Stucanet                     | -            |
|  Wood                         | -            |
|  Concrete                    | -            |
|  Concrete + plaster         | -            |
|  Lintel + plaster           | -            |
|  Hollow-core slab           | -            |
|  Hollow-core slab + plaster | -            |
|  Stretched ceiling          | -            |

### FINISH YOUR SPECIFICATION

#### Emergency units



**21032 0270 B** EMERGENCY UNIT 7W / 1h + LED INDICATOR HOLDER B

Cutout dimension (mm): 27

**21032 0270 W** EMERGENCY UNIT 7W / 1h + LED INDICATOR HOLDER W

# DELTALIGHT

## DEEP RINGO LED 92733

202 272 811 922 BRG


### LED power supplies

### # of Fixtures



# of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.

Min current | Max current




**300 48 350 ED1** LED POWER CONVERTER 48V-DC to 350 mA-DC / 15W DIM1

1

Dimtype: 1-10V

Cutout dimension (mm): 30




**300 48 350 ED5** LED POWER CONVERTER 48V-DC to 350 mA-DC / 15W DIM5

1

Dimtype: DALI

Cutout dimension (mm): 45




**300 48 350 MDL** LED POWER CONVERTER 48V-DC to 350 mA-DC / 15W MDL

1

Dimtype: non-dimmable

Cutout dimension (mm): 30




**300 48 350 WDL** LED POWER CONVERTER 48V-DC to 350 mA-DC / 15W WDL

1

Dimtype: WDL = wireless dimmable

Cutout dimension (mm): 45




**300 48 500 ED1** LED POWER CONVERTER 48V-DC to 500 mA-DC / 22W DIM1

1

Dimtype: 1-10V

Cutout dimension (mm): 30




**300 48 500 ED5** LED POWER CONVERTER 48V-DC to 500 mA-DC / 22W DIM5

1

Dimtype: DALI

Cutout dimension (mm): 45




**300 48 500 MDL** LED POWER CONVERTER 48V-DC to 500 mA-DC / 22W MDL

1

Dimtype: non-dimmable

Cutout dimension (mm): 30



**300 48 500 WDL** LED POWER CONVERTER 48V-DC to 500 mA-DC / 22W WDL

1


Dimtype: WDL = wireless dimmable

Cutout dimension (mm): 45

# DELTALIGHT

## DEEP RINGO LED 92733

202 272 811 922 BRG




**300 90 61** LED POWER SUPPLY MULTI-POWER DIM6

2 | 2

**Dimtype: mains (phase cut-off) or push button**

**Cutout dimension (mm): 56**




**300 90 63** LED POWER SUPPLY MULTI-POWER DIM9

4(4) | 4(4)

**Dimtype: 1-10V or DALI or push button**

**Cutout dimension (mm): 82**




**300 90 64** LED POWER SUPPLY MULTI-POWER DIM7

2(1) | 2(1)

**Dimtype: 1-10V or push button**


**Cutout dimension (mm): 72**



**300 90 67** LED POWER CONVERTER 24V-DC TO MULTI CURRENT 48W DIM9

2

**Dimtype: 1-10V or DALI or push button**




**300 90 68** LED POWER SUPPLY MULTI-POWER DIM5

2(2) | 2(1)

**Dimtype: DALI**

**Cutout dimension (mm): 72**




**300 90 69** LED POWER SUPPLY MULTI-POWER HV DIM9

2->6(6) | 6(4)

**Dimtype: 1-10V or DALI or push button**

**Cutout dimension (mm): 84**




**300 90 124** LED POWER SUPPLY MULTI-POWER DIM7

3(2) | 2(1)

**Dimtype: 1-10V or push button**

**Cutout dimension (mm): 55**




**300 90 125** LED POWER SUPPLY MULTI-POWER MINI DIM5

2(2) | 2(1)

**Dimtype: DALI**

**Cutout dimension (mm): 55**




**300 90 135** LED POWER SUPPLY MULTI-POWER HV

3->3 | 2->3

**Dimtype: non-dimmable**

**Cutout dimension (mm): 90**



**21012 004W** LED POWER SUPPLY MULTI-POWER WDL

3(3) | 3(3)


**Dimtype: WDL = wireless dimmable**

**Cutout dimension (mm): 84**

# DELTALIGHT

## DEEP RINGO LED 92733

202 272 811 922 BRG




**21012 005W** LED POWER SUPPLY MULTI-POWER COMPACT WDL

3 | 3

**Dimtype:** WDL = wireless dimmable

**Cutout dimension (mm):** 54



**21012 0258** LED POWER SUPPLY MULTI POWER 200-350 / 10W DIM8

1

**Dimtype:** mains (phase cut-off)

**Cutout dimension (mm):** 50



**21012 0278** LED POWER SUPPLY MULTI POWER 500-700 / 20W DIM8

1

**Dimtype:** mains (phase cut-off)

**Cutout dimension (mm):** 55



**21012 0288** LED POWER SUPPLY MULTI POWER 500-700 / 36W DIM8

2->3

**Dimtype:** mains (phase cut-off)

**Cutout dimension (mm):** 55




**21012 0298** LED POWER SUPPLY MULTI POWER 250-900 / 20W DIM8

2 | 2

**Dimtype:** mains (phase cut-off)

**Cutout dimension (mm):** 48




**21012 0480** LED POWER SUPPLY 350mA-DC / 17W IP68

2(2)

**Dimtype:** non-dimmable

**Cutout dimension (mm):** 60



**21012 0500** LED POWER SUPPLY 500mA-DC / 24W IP68

2(1)

**Dimtype:** non-dimmable

**Cutout dimension (mm):** 60



**21032 0295** LED POWER CONVERTER 48V-DC to 350 mA-DC / 15W DIM5

2

**Dimtype:** DALI

**Cutout dimension (mm):** 30



**21032 0305** LED POWER CONVERTER 48V-DC to 500 mA-DC / 22W DIM5

2

**Dimtype:** DALI

**Cutout dimension (mm):** 30

# DELTALIGHT

## **DEEP RINGO LED 92733**

202 272 811 922 BRG

Notes: