





## DEEP RINGO LED 92733

202 272 811 922 BROB

AVAILABLE IN

**BLACK** 202 272 811 922 B  
**BRUSHED ALU** 202 272 811 922 BRA  
**BRUSHED ANTHRACITE** 202 272 811 922 BRAT  
**BRUSHED BROWN BRONZE** 202 272 811 922 BRBB  
**BRUSHED COPPER** 202 272 811 922 BRCU  
**BRUSHED GOLD** 202 272 811 922 BRG  
**BRUSHED OLD BRONZE** 202 272 811 922 BROB  
**CREAM** 202 272 811 922 CR  
**FLEMISH BRONZE** 202 272 811 922 FBR  
**FLEMISH GOLD** 202 272 811 922 FG  
**GOLD COLOURED** 202 272 811 922 GC  
**PIANO BLACK** 202 272 811 922 PB  
**WHITE** 202 272 811 922 W



[View on website](#)



### General info

<b>LOCATION</b>	indoor
<b>INSTALLATION</b>	Ceiling Recessed
<b>CUTOUT SHAPE/SIZE (MM)</b>	round - 76
<b>RECESSED DEPTH (MM)</b>	90
<b>THICKNESS OF MOUNTING SURFACE (MM)</b>	min.5
<b>INGRESS PROTECTION</b>	IP20
<b>WEIGHT (KG)</b>	0.2
<b>ADJUSTABILITY</b>	non adjustable
<b>INFORMATION</b>	REFLECTOR FL-33° EXCL.LED POWER SUPPLY 350-500mA-DC

### Electrical info

<b>CLASS</b>	III
<b>DIM TYPE</b>	depending on power supply
<b>ENERGY CLASS</b>	E
<b>CERTIFICATES</b>	CB, EAC, ENEC, EPD, LCA

### Lightsource info

<b>LIGHTSOURCE NAME</b>	LED
<b>LIGHTSOURCE</b>	LED array 5,8-8,6W / CRI>90 (R9: 60) / 2700K / 753-1041lm
<b>TM-30 VALUES</b>	rf: 89 / Rg: 100
<b>SDCM</b>	SDCM1
<b>RISKGROUP</b>	RG1
<b>LM80</b>	L90B10 > 50000
<b>BEAMANGLE</b>	33°
<b>LED TECHNICS (LIGHT SOURCE)</b>	1041lm // 8,6W // 121lm/W
<b>LED TECHNICS (LUMINAIRE)</b>	768lm // 9,9W // 78lm/W

### Requirements

LED POWER SUPPLY 350 / 500mA-DC DIM

# DELTALIGHT

## DEEP RINGO LED 92733

202 272 811 922 BROB

For detailed installation instructions, please consult the manual : [202\\_272\\_811\\_XXX\\_HAND.pdf](#)

### CEILING COMPATIBILITY

Ceiling Type	Mounting Kit
 System ceiling	-
 Plasterboard	-
 Stucanet	-
 Wood	-
 Concrete	-
 Concrete + plaster	-
 Lintel + plaster	-
 Hollow-core slab	-
 Hollow-core slab + plaster	-
 Stretched ceiling	-

### FINISH YOUR SPECIFICATION

#### Emergency units



**21032 0270 B** EMERGENCY UNIT 7W / 1h + LED INDICATOR HOLDER B

Cutout dimension (mm): 27

**21032 0270 W** EMERGENCY UNIT 7W / 1h + LED INDICATOR HOLDER W

# DELTALIGHT

## DEEP RINGO LED 92733

202 272 811 922 BROB


### LED power supplies

### # of Fixtures



# of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.

Min current | Max current




**300 48 350 ED1** LED POWER CONVERTER 48V-DC to 350 mA-DC / 15W DIM1

1

Dimtype: 1-10V

Cutout dimension (mm): 30




**300 48 350 ED5** LED POWER CONVERTER 48V-DC to 350 mA-DC / 15W DIM5

1

Dimtype: DALI

Cutout dimension (mm): 45




**300 48 350 MDL** LED POWER CONVERTER 48V-DC to 350 mA-DC / 15W MDL

1

Dimtype: non-dimmable

Cutout dimension (mm): 30




**300 48 350 WDL** LED POWER CONVERTER 48V-DC to 350 mA-DC / 15W WDL

1

Dimtype: WDL = wireless dimmable

Cutout dimension (mm): 45




**300 48 500 ED1** LED POWER CONVERTER 48V-DC to 500 mA-DC / 22W DIM1

1

Dimtype: 1-10V

Cutout dimension (mm): 30




**300 48 500 ED5** LED POWER CONVERTER 48V-DC to 500 mA-DC / 22W DIM5

1

Dimtype: DALI

Cutout dimension (mm): 45




**300 48 500 MDL** LED POWER CONVERTER 48V-DC to 500 mA-DC / 22W MDL

1

Dimtype: non-dimmable

Cutout dimension (mm): 30



**300 48 500 WDL** LED POWER CONVERTER 48V-DC to 500 mA-DC / 22W WDL

1


Dimtype: WDL = wireless dimmable

Cutout dimension (mm): 45

# DELTALIGHT

## DEEP RINGO LED 92733

202 272 811 922 BROB




**300 90 61** LED POWER SUPPLY MULTI-POWER DIM6

2 | 2

Dimtype: mains (phase cut-off) or push button

Cutout dimension (mm): 56




**300 90 63** LED POWER SUPPLY MULTI-POWER DIM9

4(4) | 4(4)

Dimtype: 1-10V or DALI or push button

Cutout dimension (mm): 82




**300 90 64** LED POWER SUPPLY MULTI-POWER DIM7

2(1) | 2(1)

Dimtype: 1-10V or push button


Cutout dimension (mm): 72



**300 90 67** LED POWER CONVERTER 24V-DC TO MULTI CURRENT 48W DIM9

2

Dimtype: 1-10V or DALI or push button




**300 90 68** LED POWER SUPPLY MULTI-POWER DIM5

2(2) | 2(1)

Dimtype: DALI

Cutout dimension (mm): 72




**300 90 69** LED POWER SUPPLY MULTI-POWER HV DIM9

2->6(6) | 6(4)

Dimtype: 1-10V or DALI or push button

Cutout dimension (mm): 84




**300 90 124** LED POWER SUPPLY MULTI-POWER DIM7

3(2) | 2(1)

Dimtype: 1-10V or push button

Cutout dimension (mm): 55




**300 90 125** LED POWER SUPPLY MULTI-POWER MINI DIM5

2(2) | 2(1)

Dimtype: DALI

Cutout dimension (mm): 55




**300 90 135** LED POWER SUPPLY MULTI-POWER HV

3->3 | 2->3

Dimtype: non-dimmable

Cutout dimension (mm): 90



**21012 004W** LED POWER SUPPLY MULTI-POWER WDL

3(3) | 3(3)

Dimtype: WDL = wireless dimmable

Cutout dimension (mm): 84

# DELTALIGHT

## DEEP RINGO LED 92733

202 272 811 922 BROB



**21012 005W** LED POWER SUPPLY MULTI-POWER COMPACT WDL

3 | 3

**Dimtype:** WDL = wireless dimmable

**Cutout dimension (mm): 54**



**21012 0258** LED POWER SUPPLY MULTI POWER 200-350 / 10W DIM8

1

**Dimtype:** mains (phase cut-off)

**Cutout dimension (mm): 50**



**21012 0278** LED POWER SUPPLY MULTI POWER 500-700 / 20W DIM8

1

**Dimtype:** mains (phase cut-off)

**Cutout dimension (mm): 55**



**21012 0288** LED POWER SUPPLY MULTI POWER 500-700 / 36W DIM8

2->3

**Dimtype:** mains (phase cut-off)

**Cutout dimension (mm): 55**




**21012 0298** LED POWER SUPPLY MULTI POWER 250-900 / 20W DIM8

2 | 2

**Dimtype:** mains (phase cut-off)

**Cutout dimension (mm): 48**




**21012 0480** LED POWER SUPPLY 350mA-DC / 17W IP68

2(2)

**Dimtype:** non-dimmable

**Cutout dimension (mm): 60**



**21012 0500** LED POWER SUPPLY 500mA-DC / 24W IP68

2(1)

**Dimtype:** non-dimmable

**Cutout dimension (mm): 60**



**21032 0295** LED POWER CONVERTER 48V-DC to 350 mA-DC / 15W DIM5

2

**Dimtype:** DALI

**Cutout dimension (mm): 30**



**21032 0305** LED POWER CONVERTER 48V-DC to 500 mA-DC / 22W DIM5

2

**Dimtype:** DALI

**Cutout dimension (mm): 30**

# DELTALIGHT

## **DEEP RINGO LED 92733**

202 272 811 922 BROB

Notes: