





DIRO SBL M 82 W

202 296 82 W

AVAILABLE IN

BLACK 202 296 82 B

WHITE 202 296 82 W



[View on website](#)

General info

LOCATION	indoor
INSTALLATION	Ceiling Recessed
CUTOUT SHAPE/SIZE (MM)	round - 156
RECESSED DEPTH (MM)	70
THICKNESS OF MOUNTING SURFACE (MM)	max.25
INGRESS PROTECTION	IP43/20
WEIGHT (KG)	0.6
ADJUSTABILITY	non adjustable
INFORMATION	INCL.LED POWER SUPPLY 350mA-DC INCL.PC SBL

Electrical info

ELECTRICAL	100-240V / 50-60Hz
CLASS	II
POWER SUPPLY INCLUDED	YES
DIM TYPE	non-dimmable
ENERGY CLASS	D

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED FLEX 9,8W / CRI>80 / 2700K / 1500lm
LED TECHNICS (LIGHT SOURCE)	1500 lm // 9 W // 153 lm/W
LED TECHNICS (LUMINAIRE)	761lm // 11W // 68lm/W

For detailed installation instructions, please consult the manual: [202_296_XX_HAND.pdf](#)

DIRO SBL M 82 W
202 296 82 W

CEILING COMPATIBILITY

Ceiling Type	Mounting Kit
 System ceiling	-
 Plasterboard	-
 Stucanet	-
 Wood	-
 Stretched ceiling	-

Notes: