



## SUPERLOOP SLIM DOWN 120 SBL 930

20582 9300 W

AVAILABLE IN



**BLACK** 20582 9300 B

**FLEMISH BRONZE** 20582 9300 FBR

**FLEMISH GOLD** 20582 9300 FG

**GOLD COLOURED** 20582 9300 GC

**WHITE** 20582 9300 W



 [View on website](#)



### General info

<b>LOCATION</b>	indoor
<b>INSTALLATION</b>	Ceiling Suspended
<b>INGRESS PROTECTION</b>	IP20
<b>WEIGHT (KG)</b>	2.5
<b>ADJUSTABILITY</b>	non adjustable
<b>INFORMATION</b>	INCL.PC SBL EXCL.LED POWER SUPPLY 900-1200mA-DC INCL.3 x CABLE SUSPENSION SINGLE AUTO. 3.0m INCL.1 x CABLE 2 x 0.75mm <sup>2</sup>

### Electrical info

<b>CLASS</b>	III
<b>DIM TYPE</b>	depending on power supply
<b>ENERGY CLASS</b>	E
<b>CERTIFICATES</b>	CB, ENEC, EPD

### Lightsource info

<b>LIGHTSOURCE NAME</b>	LED
<b>LIGHTSOURCE</b>	LED cluster 36,4-50,3W / CRI>90 (R9: 59) / 3000K / 5022-6665lm
<b>SDCM</b>	SDCM3
<b>LM80</b>	L70 > 30000
<b>LED TECHNICS (LIGHT SOURCE)</b>	6665lm // 50,3W // 132lm/W
<b>LED TECHNICS (LUMINAIRE)</b>	2951lm // 57,8W // 51lm/W

### Requirements

LED POWER SUPPLY 900 / 1200mA-DC DIM  
SUPERLOOP POWERBOX H 900mA  
SUPERLOOP POWERBOX H 1200mA

### Options

CABLE BASE R / S  
COVERSET R 62-90-100 / S 62-80-90  
CONNECTION ST / CONNECTION TRIMLESS  
SUSPENSION ST / SUSPENSION TRIMLESS

# DELTALIGHT


## SUPERLOOP SLIM DOWN 120 SBL 930

20582 9300 W

For detailed installation instructions, please consult the manual : [20582\\_XXX0\\_HAND.pdf](#)

### FINISH YOUR SPECIFICATION

#### Current supply



**203 99 55 ANO** CABLE BASE R ANO

**203 99 55 B** CABLE BASE R B

**203 99 55 W** CABLE BASE R W



**203 99 56 ANO** CABLE BASE S ANO

**203 99 56 B** CABLE BASE S B

**203 99 56 W** CABLE BASE S W


#### Power box

#### # of Fixtures



# of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.

Min current | Max current




**321 55 312 ED1 B** SUPERLOOP POWERBOX H8 1200mA DIM1 B

1

Dimtype: 1-10V

**321 55 312 ED1 W** SUPERLOOP POWERBOX H8 1200mA DIM1 W

1



**20548 0015 B** SUPERLOOP POWERBOX H9 900mA DIM5 B

1

Dimtype: DALI


# DELTALIGHT

## SUPERLOOP SLIM DOWN 120 SBL 930

20582 9300 W

**20548 0015 W** SUPERLOOP POWERBOX H9 900mA DIM5 W

1



**20548 0025 B** SUPERLOOP POWERBOX H9 1200mA DIM5 B

1

Dimtype: DALI

**20548 0025 W** SUPERLOOP POWERBOX H9 1200mA DIM5 W


1

### LED power supplies

### # of Fixtures

**i** # of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.

Min current | Max current




**300 90 129** LED POWER SUPPLY 900mA-DC / 60W DIM5

1

Dimtype: DALI

Cutout dimension (mm): 84




**300 90 130** LED POWER SUPPLY 1200mA-DC / 60W DIM5

1

Dimtype: DALI

Cutout dimension (mm): 95




**300 90 132** LED POWER SUPPLY 1200mA-DC / 70W DIM1

1

Dimtype: 1-10V

Cutout dimension (mm): 80

### Coversets



**204 00 62 ANO** COVERSET R 62 ANO


**204 00 62 B** COVERSET R 62 B

**204 00 62 W** COVERSET R 62 W

# DELTALIGHT

## SUPERLOOP SLIM DOWN 120 SBL 930


20582 9300 W



**204 00 90 ANO** COVERSET R 90 ANO

**204 00 90 B** COVERSET R 90 B


**204 00 90 W** COVERSET R 90 W



**204 00 100 ANO** COVERSET R 100 ANO

**204 00 100 B** COVERSET R 100 B


**204 00 100 W** COVERSET R 100 W



**204 62 62 ANO** COVERSET S 62 ANO

**204 62 62 B** COVERSET S 62 B


**204 62 62 W** COVERSET S 62 W



**204 80 80 ANO** COVERSET S 80 ANO

**204 80 80 B** COVERSET S 80 B

**204 80 80 W** COVERSET S 80 W



**204 90 90 ANO** COVERSET S 90 ANO

**204 90 90 B** COVERSET S 90 B

**204 90 90 W** COVERSET S 90 W


# DELTALIGHT

## SUPERLOOP SLIM DOWN 120 SBL 930

20582 9300 W

### Suspension parts

---



**328 10 01** SUSPENSION TRIMLESS O.F.A.

Cutout dimension (mm): 62 (CONCRETE: 102)

---



**15225 0340 B** SUSPENSION ST B


Cutout dimension (mm): 27

---

**15225 0340 W** SUSPENSION ST W

### Electric connection parts

---



**328 10 03** CONNECTION TRIMLESS O.F.A.

Cutout dimension (mm): 62 (CONCRETE: 102)

---



**15225 0360 B** CONNECTION ST B

Cutout dimension (mm): 43

---

**15225 0360 W** CONNECTION ST W

Notes: