





SUPER-OH! SLIM 80 SBL DOWN 930 B

20737 9300 B

AVAILABLE IN

BLACK 20737 9300 B

WHITE 20737 9300 W



[View on website](#)

General info

LOCATION	indoor
INSTALLATION	Ceiling Surface mounted
INGRESS PROTECTION	IP20
WEIGHT (KG)	3,6
ADJUSTABILITY	non adjustable
INFORMATION	INCL.PC SBL INCL.LED POWER SUPPLY 900mA

Electrical info

ELECTRICAL	220-240V / 50-60Hz
CLASS	I
POWER SUPPLY	YES
DIM TYPE	non-dimmable
ENERGY CLASS	C
CERTIFICATES	CB, ENEC, RCM

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED cluster 28,6W / CRI>90 (R9: 50) / 3000K / 4570lm
SDCM	SDCM3
LM80	L80 > 60000
LED TECHNICS (LIGHT SOURCE)	4570lm // 28,6W // 159lm/W
LED TECHNICS (LUMINAIRE)	2961lm // 33W // 90lm/W

Options

SUSPENSION SET 28 3x0,75 3m

CABLE BASE R / S

COVERSET R 62-90-100 / S 62-80-90


For detailed installation instructions, please consult the manual: [20737_XXX0_HAND.pdf](#)

SUPER-OH! SLIM 80 SBL DOWN 930 B

20737 9300 B

FINISH YOUR SPECIFICATION

Current supply



41 **203 99 55 ANO** CABLE BASE R ANO

☐

203 99 55 B CABLE BASE R B

☐

203 99 55 W CABLE BASE R W

☐

41 **203 99 56 ANO** CABLE BASE S ANO

☐


203 99 56 B CABLE BASE S B

☐

203 99 56 W CABLE BASE S W

☐

Coversets



204 00 100 B COVERSET R 100 B

☐

204 00 100 W COVERSET R 100 W

☐

SUPER-OH! SLIM 80 SBL DOWN 930 B
20737 9300 B

Suspension parts



15225 0280 B SUSPENSION SET 28 3x0,75 3m B

☐

15225 0280 W SUSPENSION SET 28 3x0,75 3m W

☐

Electric connection parts



15225 0360 B CONNECTION ST B

☐

15225 0360 W CONNECTION ST W

☐

Notes: