





SUPER-OH! SLIM 80 C SBL DOWN-UP 930 DIM4 W

20739 9304 W

AVAILABLE IN

BLACK 20739 9304 B

WHITE 20739 9304 W



[View on website](#)



General info

LOCATION	indoor
INSTALLATION	Ceiling Suspended
INGRESS PROTECTION	IP20
WEIGHT (KG)	4.3
ADJUSTABILITY	non adjustable
INFORMATION	INCL.PC SBL DOWN: INCL.DIMMABLE LED POWER SUPPLY 900mA UP: INCL.DIMMABLE LED POWER SUPPLY 700mA INCL.4 x CABLE SUSPENSION SINGLE AUTO. 3m INCL.1 x CABLE 5 x 0.75mm ² CABLING 2 CIRCUITS

Electrical info

ELECTRICAL	220-240V / 0 50-60Hz
CLASS	I
POWER SUPPLY INCLUDED	YES
DIM TYPE	DALI or DSI or push button
ENERGY CLASS	D

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	DOWN: LED cluster 28,6W / CRI>90 (R9: 50) / 3000K / 4570lm UP: LED cluster 22,3W / CRI>90 (R9: 50) / 3000K / 3542lm
SDCM	SDCM3
LM80	L80 > 60000
LED TECHNICS (LIGHT SOURCE)	DOWN: 4570lm // 28,6W // 159lm/W UP: 3542lm // 22,3W // 159lm/W
LED TECHNICS (LUMINAIRE)	DOWN: 2961lm // 33W // 90lm/W UP: 2699lm // 26W // 105lm/W

Options

CABLE BASE R / S
COVERSET R 62-90-100 / S 62-80-90
CONNECTION ST / CONNECTION TRIMLESS
SUSPENSION ST / SUSPENSION TRIMLESS



SUPER-OH! SLIM 80 C SBL DOWN-UP 930 DIM4 W

20739 9304 W

For detailed installation instructions, please consult the manual: [20739_XXX4_HAND.pdf](#)

SUPER-OH! SLIM 80 C SBL DOWN-UP 930 DIM4 W
20739 9304 W

FINISH YOUR SPECIFICATION

Current supply



41

203 99 55 ANO CABLE BASE R ANO

☐

203 99 55 B CABLE BASE R B

☐

203 99 55 W CABLE BASE R W

☐



41

203 99 56 ANO CABLE BASE S ANO

☐

203 99 56 B CABLE BASE S B

☐

203 99 56 W CABLE BASE S W

☐

Coversets



204 00 100 B COVERSET R 100 B

☐

204 00 100 W COVERSET R 100 W

☐

SUPER-OH! SLIM 80 C SBL DOWN-UP 930 DIM4 W
20739 9304 W

Suspension parts



328 10 01 SUSPENSION TRIMLESS O.F.A.

☐



15225 0340 B SUSPENSION ST B

☐

15225 0340 W SUSPENSION ST W

☐

Electric connection parts



328 10 03 CONNECTION TRIMLESS O.F.A.

☐



15225 0360 B CONNECTION ST B

☐

15225 0360 W CONNECTION ST W

☐

Notes: