DELTALIGHT®

# LOGIC 60 R MOON 93020 ANO

213 45 10 811 932 ANO

AVAILABLE IN
**ALU ANODIZED** 213 45 10 811 932 ANO







View on website

| General info | |
|---|---|
| **LOCATION** | outdoor |
| **INSTALLATION** | Floor Recessed |
| **CUTOUT SHAPE/SIZE (MM)** | round - 61 |
| **RECESSED DEPTH (MM)** | 100 |
| **INGRESS PROTECTION** | IP67 |
| **PROTECTION AGAINST MECHANICAL IMPACT** | IK08 |
| **WEIGHT (KG)** | 0.5 |
| **ADJUSTABILITY** | non adjustable |
| **INFORMATION** | REFLECTOR FL-20°<br>INCL.1 x CABLE H05 RN-F 2 x 1mm² 0,5m<br>EXCL.LED POWER SUPPLY 350mA-DC<br>IEC 60598-2-13 : max.150kg 25N/cm²<br>ESG 5mm |

| Electrical info | |
|---|---|
| **CLASS** | III |
| **DIM TYPE** | depending on power supply |
| **ENERGY CLASS** | D |
| **CERTIFICATES** | CB, EAC, ENEC |

| Lightsource info | |
|---|---|
| **LIGHTSOURCE NAME** | LED |
| **LIGHTSOURCE** | LED array 5,8W / CRI>90 (R9: 52) / 3000K / 787lm |
| **TM-30 VALUES** | rf: 90 / Rg: 99 |
| **SDCM** | SDCM1 |
| **RISKGROUP** | RG1 |
| **LM80** | L90B10 > 50000 |
| **LED TECHNICS (LIGHT SOURCE)** | 787lm // 5,8W // 135lm/W |
| **LED TECHNICS (LUMINAIRE)** | 353lm // 7W // 53lm/W |

**Requirements**

LED POWER SUPPLY 350mA-DC DIM

DELTALIGHT®

# LOGIC 60 R MOON 93020 ANO

213 45 10 811 932 ANO

**Options**

LOGIC 60 BOX R
CBOX
IP68 CONNECTION KIT
IP68 CONNECTOR 3P

For detailed installation instructions, please consult the manual: **213_45_10_811_XXX_HAND.pdf**

DELTALIGHT®

# LOGIC 60 R MOON 93020 ANO

213 45 10 811 932 ANO

## FINISH YOUR SPECIFICATION

| LED power supplies | | | # |
|---|---|---|---|
|  | **300 90 63** | LED POWER SUPPLY MULTI-POWER DIM9 | 1->4(4) ☐ |
|  | **300 90 68** | LED POWER SUPPLY MULTI-POWER DIM5 | 1->2(1) ☐ |
|  | **300 90 69** | LED POWER SUPPLY MULTI-POWER HV DIM9 | 2->6(6) ☐ |
|  | **300 90 124** | LED POWER SUPPLY MULTI-POWER DIM7 | 2(2) ☐ |
|  | **300 90 125** | LED POWER SUPPLY MULTI-POWER MINI DIM5 | 2(2) ☐ |
|  | **21012 0010** | LED POWER SUPPLY MULTI POWER | 1->2 ☐ |
|  | **21012 0021** | LED POWER SUPPLY MULTI POWER DIM1 | 1->2 ☐ |
|  | **21012 0035** | LED POWER SUPPLY MULTI POWER DIM5 | 1->2 ☐ |
|  | **21012 005W** | LED POWER SUPPLY MULTI-POWER COMPACT WDL | 1->2 ☐ |

DELTALIGHT®

# LOGIC 60 R MOON 93020 ANO

213 45 10 811 932 ANO




**21012 0258** LED POWER SUPPLY MULTI POWER 200-350 / 10W DIM8 — 1




**21012 0298** LED POWER SUPPLY MULTI POWER 250-900 / 20W DIM8 — 2




**21012 0480** LED POWER SUPPLY 350mA-DC / 17W IP68 — 1-2(2)




**21032 0295** LED POWER CONVERTER 48V-DC to 350 mA-DC / 15W DIM5 — 1

## Ground mounting boxes




**213 19 10** LOGIC 60 BOX R

DELTALIGHT®

# LOGIC 60 R MOON 93020 ANO

213 45 10 811 932 ANO

| Waterproof connection parts | # |
|---|---|
|   **216 12 00** CBOX | |
|   **216 12 01** IP68 CONNECTION KIT | |
| **216 12 02** IP68 CONNECTOR 3P | |
|   **216 14 35** CBOX 350 mA / 10W | 1 |

Notes: