





## LOGIC 60 R WALLWASH SBL ANO

213 45 2125 ANO

AVAILABLE IN  
**ALU ANODIZED** 213 45 2125 ANO



[View on website](#)



### General info

<b>LOCATION</b>	outdoor
<b>INSTALLATION</b>	Floor Recessed
<b>CUTOUT SHAPE/SIZE (MM)</b>	round - 61
<b>RECESSED DEPTH (MM)</b>	100
<b>INGRESS PROTECTION</b>	IP67
<b>PROTECTION AGAINST MECHANICAL IMPACT</b>	IK08
<b>WEIGHT (KG)</b>	0.5
<b>ADJUSTABILITY</b>	non adjustable
<b>INFORMATION</b>	INCL.CABLE H05 RN-F 2 x 1mm <sup>2</sup> 0,5m EXCL.LED POWER SUPPLY 24V-DC IEC 60598-2-13 : max.150kg 25N/cm <sup>2</sup> ESG 5mm

### Electrical info

<b>ELECTRICAL</b>	24V-DC
<b>CLASS</b>	III
<b>DIM TYPE</b>	non-dimmable
<b>ENERGY CLASS</b>	G
<b>CERTIFICATES</b>	CB

### Lightsource info

<b>LIGHTSOURCE NAME</b>	LED
<b>LIGHTSOURCE</b>	LED 4W / CRI>80 / 3000K / 335lm
<b>LED TECHNICS (LIGHT SOURCE)</b>	335lm // 4W // 84lm/W
<b>LED TECHNICS (LUMINAIRE)</b>	139lm // 5W // 30lm/W

### Requirements

LED POWER SUPPLY 24V-DC

### Options

LOGIC 60 BOX R  
CBOX  
IP68 CONNECTION KIT  
IP68 CONNECTOR 3P



## **LOGIC 60 R WALLWASH SBL ANO**

213 45 2125 ANO

For detailed installation instructions, please consult the manual: [\*\*213\\_45\\_2125\\_HAND.pdf\*\*](#)


## LOGIC 60 R WALLWASH SBL ANO

213 45 2125 ANO

### FINISH YOUR SPECIFICATION


#### LED power supplies

#



**300 89 24 150** LED POWER SUPPLY 24V-DC / 150W

33


☐


**21012 0160** LED POWER SUPPLY 24V-DC / 24W

5

☐


#### Ground mounting boxes




**213 19 10** LOGIC 60 BOX R

☐


#### Waterproof connection parts



**216 12 00** CBOX

☐


**216 12 01** IP68 CONNECTION KIT

☐


**216 12 02** IP68 CONNECTOR 3P

☐

**LOGIC 60 R WALLWASH SBL ANO**

213 45 2125 ANO

Notes: