





## LOGIC 90 R WALLWASH 930 SBL ANO

213 474 811 930 ANO

AVAILABLE IN  
**ALU ANODIZED** 213 474 811 930 ANO



[View on website](#)

### General info

<b>LOCATION</b>	outdoor
<b>INSTALLATION</b>	Floor Recessed
<b>CUTOUT SHAPE/SIZE (MM)</b>	round - 93
<b>RECESSED DEPTH (MM)</b>	125
<b>INGRESS PROTECTION</b>	IP67
<b>PROTECTION AGAINST MECHANICAL IMPACT</b>	IK07
<b>WEIGHT (KG)</b>	1
<b>ADJUSTABILITY</b>	non adjustable
<b>INFORMATION</b>	INCL.CABLE H05 RN-F 2 x 1mm² 0,5m INCL.LED POWER SUPPLY 350mA-DC INCL.IP68 CONNECTOR 3P IEC 60598-2-13 : max.150kg 25N/cm² ESG 5mm

### Electrical info

<b>ELECTRICAL</b>	100-240V / 50-60Hz
<b>CLASS</b>	II
<b>POWER SUPPLY</b>	YES
<b>DIM TYPE</b>	non-dimmable
<b>ENERGY CLASS</b>	D

### Lightsource info

<b>LIGHTSOURCE NAME</b>	LED
<b>LIGHTSOURCE</b>	LED array 5,8W / CRI>90 (R9: 52) / 3000K / 787lm
<b>TM-30 VALUES</b>	Rf: 90 / Rg: 99
<b>SDCM</b>	SDCM1
<b>RISKGROUP</b>	RG1
<b>LM80</b>	L90B10 > 50000
<b>LED TECHNICS (LIGHT SOURCE)</b>	787lm // 5,8W // 135lm/W
<b>LED TECHNICS (LUMINAIRE)</b>	401lm // 7W // 60lm/W

### Options

LOGIC 90 BOX R  
CBOX


**LOGIC 90 R WALLWASH 930 SBL ANO**

213 474 811 930 ANO

For detailed installation instructions, please consult the manual: [213\\_474\\_811\\_XXX\\_HAND.pdf](#)

**FINISH YOUR SPECIFICATION**


**Ground mounting boxes**



**213 19 09** LOGIC 90 BOX R

☐

**Waterproof connection parts**



**216 12 00** CBOX

☐

Notes: