





LOGIC 90 R A WALLWASH 930 SBL B

213 484 811 930 B

AVAILABLE IN
ALU ANODIZED 213 484 811 930 ANO
BLACK 213 484 811 930 B



[View on website](#)

| General info | |
|--------------------------------------|--|
| LOCATION | outdoor |
| INSTALLATION | Floor Recessed |
| CUTOUT SHAPE/SIZE (MM) | round - 93 |
| RECESSED DEPTH (MM) | 125 |
| INGRESS PROTECTION | IP67 |
| PROTECTION AGAINST MECHANICAL IMPACT | IK07 |
| WEIGHT (KG) | 1 |
| ADJUSTABILITY | non adjustable |
| INFORMATION | INCL.CABLE H05 RN-F 2 x 1mm² 0,5m INCL.LED POWER SUPPLY 350mA-DC INCL.IP68 CONNECTOR 3P IEC 60598-2-13 : max.150kg 25N/cm² ESG 5mm |

| Electrical info | |
|-----------------|--------------------|
| ELECTRICAL | 100-240V / 50-60Hz |
| CLASS | II |
| POWER SUPPLY | YES |
| DIM TYPE | non-dimmable |
| ENERGY CLASS | D |

| Lightsource info | |
|-----------------------------|--|
| LIGHTSOURCE NAME | LED |
| LIGHTSOURCE | LED array 5,8W / CRI>90 (R9: 52) / 3000K / 787lm |
| TM-30 VALUES | Rf: 90 / Rg: 99 |
| SDCM | SDCM1 |
| RISKGROUP | RG1 |
| LM80 | L90B10 > 50000 |
| LED TECHNICS (LIGHT SOURCE) | 787lm // 5,8W // 135lm/W |
| LED TECHNICS (LUMINAIRE) | 401lm // 7W // 60lm/W |

| Options | |
|----------------|--|
| LOGIC 90 BOX R | |
| CBOX | |

LOGIC 90 R A WALLWASH 930 SBL B
213 484 811 930 B

For detailed installation instructions, please consult the manual: [213_484_811_XXX_HAND.pdf](#)

FINISH YOUR SPECIFICATION

Ground mounting boxes




213 19 09

 LOGIC 90 BOX R

☐

Waterproof connection parts



216 12 00

 CBOX

☐

Notes: