



STRIPER A

223 00 12 A

AVAILABLE IN
ALU GREY 223 00 12 A
ANTHRACITE (DARK GREY) 223 00 12 N



 [View on website](#)

General info

LOCATION	outdoor
INSTALLATION	Floor Surface mounted
INGRESS PROTECTION	IP55
PROTECTION AGAINST MECHANICAL IMPACT	IK06
WEIGHT (KG)	1
ADJUSTABILITY	non adjustable
INFORMATION	LENS 4° INCL.LED POWER SUPPLY 700mA-DC

Electrical info

ELECTRICAL	120-240V / 50-60Hz
CLASS	II
POWER SUPPLY INCLUDED	YES
DIM TYPE	non-dimmable
ENERGY CLASS	D
CERTIFICATES	CB, ENEC

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED cluster 2W / CRI>80 (R9: 6) / 3000K / 245lm
TM-30 VALUES	Rf: 86 / Rg: 95
SDCM	SDCM3
RISKGROUP	RG2
LM80	L90B10 > 120000
LED TECHNICS (LIGHT SOURCE)	245lm // 2W // 123lm/W
LED TECHNICS (LUMINAIRE)	245lm // 2W // 107lm/W

Options

PIN 1
PLATE 1
CBOX
IP68 CONNECTION KIT
IP68 CONNECTOR 3P

Accessories

KAP STRIPER
Delta Light NV may revise the information and technical data at any time without notice. Version: 01/02/2024


For detailed installation instructions, please consult the manual: [**223_00_12_HAND.pdf**](#)

STRIPER A

223 00 12 A

FINISH YOUR SPECIFICATION

Waterproof connection parts



216 12 00 CBOX

☐



216 12 01 IP68 CONNECTION KIT


☐



216 12 02 IP68 CONNECTOR 3P


☐

Pins and plates for bollards



229 01 01 PIN 1


☐



229 02 01 PLATE 1

☐

Light altering devices



223 00 10 B KAP STRIPER B

☐



STRIPER A

223 00 12 A

Notes: