

MONO II DOWN-UP LED 930 A

223 53 812 930 A

AVAILABLE IN



ALU GREY 223 53 812 930 A

BLACK 223 53 812 930 B

FLEMISH BRONZE OUTDOOR 223 53 812 930 FBRX

ANTHRACITE (DARK GREY) 223 53 812 930 N

WHITE 223 53 812 930 W



[View on website](#)

General info

LOCATION	outdoor
INSTALLATION	Wall Surface mounted
INGRESS PROTECTION	IP54
PROTECTION AGAINST MECHANICAL IMPACT	IK03
WEIGHT (KG)	0.7
ADJUSTABILITY	non adjustable
INFORMATION	INCL.2 x LENS INCL.LED POWER SUPPLY 350 mA-DC

Electrical info

ELECTRICAL	100-240V / 50-60Hz
CLASS	II
POWER SUPPLY	YES
DIM TYPE	non-dimmable
ENERGY CLASS	D
CERTIFICATES	CB, EAC, RCM

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	2 x (LED array 5,8W / CRI>90 (R9: 52) / 3000K / 787lm)
TM-30 VALUES	Rf: 90 / Rg: 99
SDCM	SDCM1
RISKGROUP	RG1
LM80	L90B10 > 50000
LED TECHNICS (LIGHT SOURCE)	1574lm // 11,6W // 135lm/W
LED TECHNICS (LUMINAIRE)	1280lm // 13W // 96lm/W

For detailed installation instructions, please consult the manual: [223 53 812 XXX HAND.pdf](#)



MONO II DOWN-UP LED 930 A

223 53 812 930 A

Notes: