





HALOSCAN ST MP 92735 B
23111 9230 B

AVAILABLE IN
BLACK 23111 9230 B
WHITE 23111 9230 W



 [View on website](#)

General info	
LOCATION	indoor
INSTALLATION	Ceiling Recessed
CUTOUT SHAPE/SIZE (MM)	round - 70
RECESSED DEPTH (MM)	55
THICKNESS OF MOUNTING SURFACE (MM)	min.1
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.3
ADJUSTABILITY	0° to 45° swiveling, 355° rotatable
INFORMATION	LENS FL-35° EXCL.LED POWER SUPPLY 350-500mA-DC

Electrical info	
CLASS	III
DIM TYPE	depending on type of external power supply
ENERGY CLASS	E
CERTIFICATES	CB, ENEC

Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 5,8-8,6W / CRI>90 (R9: 60) / 2700K / 753-1041lm
TM-30 VALUES	Rf: 89 / Rg: 100
SDCM	SDCM1
RISKGROUP	RG1
LM80	L90B10 > 50000
LED TECHNICS (LIGHT SOURCE)	1041lm // 8,6W // 121lm/W
LED TECHNICS (LUMINAIRE)	799lm // 10W // 81lm/W









Requirements	
LED POWER SUPPLY 350 / 500mA-DC DIM	

Accessories	
HALOSCAN HONEYCOMB HALOSCAN LINEAR SPREAD LENS	

HALOSCAN ST MP 92735 B
23111 9230 B

For detailed installation instructions, please consult the manual: [23111_XXX0_HAND.pdf](#)

CEILING COMPATIBILITY


Ceiling Type	Mounting Kit
 System ceiling	-
 Plasterboard	-
 Wood	-
 Concrete	-
 Concrete + plaster	-
 Lintel + plaster	-
 Hollow-core slab + plaster	-
 Stretched ceiling	-

HALOSCAN ST MP 92735 B

23111 9230 B

FINISH YOUR SPECIFICATION

Emergency units



21032 0270 B EMERGENCY UNIT 7W / 1h + LED INDICATOR HOLDER B










☐

21032 0270 W EMERGENCY UNIT 7W / 1h + LED INDICATOR HOLDER W

☐











HALOSCAN ST MP 92735 B

23111 9230 B

LED power supplies			#
	300 90 63	LED POWER SUPPLY MULTI-POWER DIM9	1->4(4) / 1->3(3) <input type="checkbox"/>
	300 90 68	LED POWER SUPPLY MULTI-POWER DIM5	1->2(2) / 1->2(1) <input type="checkbox"/>
	300 90 69	LED POWER SUPPLY MULTI-POWER HV DIM9	2->6(6) / 1->6(4) <input type="checkbox"/>
	300 90 124	LED POWER SUPPLY MULTI-POWER DIM7	1->2(2) / 1->2(1) <input type="checkbox"/>
	300 90 125	LED POWER SUPPLY MULTI-POWER MINI DIM5	1->2(2) / 1->2(1) <input type="checkbox"/>
	21012 0010	LED POWER SUPPLY MULTI POWER	1->2 / 1->2 <input type="checkbox"/>
	21012 0021	LED POWER SUPPLY MULTI POWER DIM1	1->3 / 1->2 <input type="checkbox"/>
	21012 0035	LED POWER SUPPLY MULTI POWER DIM5	1->3 / 1->2 <input type="checkbox"/>
	21012 005W	LED POWER SUPPLY MULTI-POWER COMPACT WDL	1->3 / 1->2 <input type="checkbox"/>

HALOSCAN ST MP 92735 B

23111 9230 B

	21012 0268 LED POWER SUPPLY MULTI POWER 200-350 / 15W DIM8	2->2 / 2->2 <input type="checkbox"/>
	21012 0278 LED POWER SUPPLY MULTI POWER 500-700 / 20W DIM8	1 <input type="checkbox"/>
	21012 0288 LED POWER SUPPLY MULTI POWER 500-700 / 36W DIM8	2->2 <input type="checkbox"/>
	21012 0298 LED POWER SUPPLY MULTI POWER 250-900 / 20W DIM8	1->2 / 1->2 / 1->2 <input type="checkbox"/>
	21012 0308 LED POWER SUPPLY 350mA / 7,35W DIM8	1 <input type="checkbox"/>
	21012 0318 LED POWER SUPPLY 500mA / 10W DIM8	1 <input type="checkbox"/>
	21012 0480 LED POWER SUPPLY 350mA-DC / 17W IP68	1-2(2) <input type="checkbox"/>
	21012 0500 LED POWER SUPPLY 500mA-DC / 24W IP68	1-2(1) <input type="checkbox"/>
	21032 0295 LED POWER CONVERTER 48V-DC to 350 mA-DC / 15W DIM5	1->2 <input type="checkbox"/>
	21032 0305 LED POWER CONVERTER 48V-DC to 500 mA-DC / 22W DIM5	1->2 <input type="checkbox"/>

HALOSCAN ST MP 92735 B

23111 9230 B


Light altering devices



² **23110 0040** HALOSCAN LINEAR SPREAD LENS

Ø72

☐



² **23110 0050 B** HALOSCAN HONEYCOMB B

Ø72

☐

Notes: