



## HALOSCAN ON 2 MP 92735 DIM8 B-B



23149 9238 B-B

AVAILABLE IN

**BLACK-BLACK** 23149 9238 B-B

**BLACK-GOLD COLORED** 23149 9238 B-GC

**WHITE-WHITE** 23149 9238 W-W



[View on website](#)

### General info

<b>LOCATION</b>	indoor
<b>INSTALLATION</b>	Ceiling Surface mounted
<b>INGRESS PROTECTION</b>	IP20
<b>WEIGHT (KG)</b>	0.7
<b>ADJUSTABILITY</b>	0° to 45° swiveling, 355° rotatable
<b>INFORMATION</b>	LENS FL-35° INCL.DIMMABLE LED POWER SUPPLY 350mA-DC

### Electrical info

<b>ELECTRICAL</b>	220-240V / 50-60Hz
<b>CLASS</b>	I
<b>POWER SUPPLY</b>	YES
<b>DIM TYPE</b>	mains (phase cut-off)
<b>ENERGY CLASS</b>	D
<b>CERTIFICATES</b>	RCM

### Lightsource info

<b>LIGHTSOURCE NAME</b>	LED
<b>LIGHTSOURCE</b>	2 x (LED array 5,8W / CRI>90 (R9: 60) / 2700K / 753lm)
<b>TM-30 VALUES</b>	Rf: 89 / Rg: 100
<b>SDCM</b>	SDCM1
<b>RISKGROUP</b>	RG1
<b>LM80</b>	L90B10 > 50000
<b>LED TECHNICS (LIGHT SOURCE)</b>	1506lm // 11,6W // 129lm/W
<b>LED TECHNICS (LUMINAIRE)</b>	1156lm // 13W // 87lm/W

### Accessories

HALOSCAN HONEYCOMB  
HALOSCAN LINEAR SPREAD LENS  
HALOSCAN KAP MP


HALOSCAN ON 2 MP 92735 DIM8 B-B

23149 9238 B-B

For detailed installation instructions, please consult the manual: [23149\\_XXX8\\_HAND.pdf](#)


FINISH YOUR SPECIFICATION

Light altering devices




**23110 0040**

HALOSCAN LINEAR SPREAD LENS

☐

**23110 0050 B**

HALOSCAN HONEYCOMB B

☐

**23110 0060 B**

HALOSCAN KAP MP B

☐

**23110 0060 W**

HALOSCAN KAP MP W

☐

Notes: