




HALOSCAN ON 2 MP 92735 DIM8 B-B

23149 9238 B-B

AVAILABLE IN
BLACK-BLACK 23149 9238 B-B
BLACK-GOLD COLORED 23149 9238 B-GC
WHITE-WHITE 23149 9238 W-W



 [View on website](#)

General info	
LOCATION	indoor
INSTALLATION	Ceiling Surface mounted
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.7
ADJUSTABILITY	0° to 45° swiveling, 355° rotatable
INFORMATION	LENS FL-35° INCL.DIMMABLE LED POWER SUPPLY 350mA-DC

Electrical info	
ELECTRICAL	220-240V / 50-60Hz
CLASS	I
POWER SUPPLY	YES
DIM TYPE	mains (phase cut-off)
ENERGY CLASS	D
CERTIFICATES	RCM




Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	2 x (LED array 5,8W / CRI>90 (R9: 60) / 2700K / 753lm)
TM-30 VALUES	rf: 89 / Rg: 100
SDCM	SDCM1
RISKGROUP	RG1
LM80	L90B10 > 50000
LED TECHNICS (LIGHT SOURCE)	1506lm // 11,6W // 129lm/W
LED TECHNICS (LUMINAIRE)	1156lm // 13W // 87lm/W

Accessories	
HALOSCAN HONEYCOMB	
HALOSCAN LINEAR SPREAD LENS	
HALOSCAN KAP MP	

For detailed installation instructions, please consult the manual: [23149_XXX8_HAND.pdf](#)

FINISH YOUR SPECIFICATION

Light altering devices

	23110 0040 HALOSCAN LINEAR SPREAD LENS	<input type="checkbox"/>
	23110 0050 B HALOSCAN HONEYCOMB B	<input type="checkbox"/>
	23110 0060 B HALOSCAN KAP MP B	<input type="checkbox"/>
	23110 0060 W HALOSCAN KAP MP W	<input type="checkbox"/>

Notes: