
DELTALIGHT




MONTUR L P 45 LED 930 DIM8

REFERENCE 14711 9308 B

AVAILABLE IN
BLACK 14711 9308 B
ANTHRACITE 14711 9308 N





View on website

General info	
LOCATION	outdoor
INSTALLATION	Floor Surface mounted
INGRESS PROTECTION	IP54
PROTECTION AGAINST MECHANICAL IMPACT	IK03
WEIGHT (KG)	1.6
ADJUSTABILITY	non adjustable
INFORMATION	INCL.DIMMABLE LED POWER SUPPLY 500mA-DC

Electrical info	
ELECTRICAL	220-240V / 50-60Hz
CLASS	II
POWER SUPPLY	YES
DIM TYPE	mains (phase cut-off)
ENERGY CLASS	E

Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED cluster 11,6W / CRI>90 / 3000K / 1632lm
LED TECHNICS (LIGHT SOURCE)	1632lm // 11,6W // 141lm/W
LED TECHNICS (LUMINAIRE)	1007lm // 13W // 75lm/W

Options

PLATE 3
CBOX
IP68 CONNECTION KIT
IP68 CONNECTOR 3P

For detailed installation instructions, please consult the manual : **14711_XXX8_HAND.pdf**


DELTALIGHT

MONTUR L P 45 LED 930 DIM8

14711 9308 B


FINISH YOUR SPECIFICATION

Waterproof connection parts



216 12 00 CBOX

Cutout dimension (mm): 142 x 142




216 12 01 IP68 CONNECTION KIT



216 12 02 IP68 CONNECTOR 3P

Pins and plates for bollards



229 02 03 PLATE 3

Notes: