



## M26L - SPY 391 92740 MDL

23258 9230 B

AVAILABLE IN

**BLACK** 23258 9230 B

**BRUSHED ALU** 23258 9230 BRA

**BRUSHED ANTHRACITE** 23258 9230 BRAT

**BRUSHED COPPER** 23258 9230 BRCU

**BRUSHED GOLD** 23258 9230 BRG

**BRUSHED OLD BRONZE** 23258 9230 BROB



**FLEMISH BRONZE** 23258 9230 FBR

**FLEMISH GOLD** 23258 9230 FG

**GOLD COLOURED** 23258 9230 GC

**PIANO BLACK** 23258 9230 PB

**WHITE** 23258 9230 W



[View on website](#)



### General info

<b>LOCATION</b>	indoor
<b>INSTALLATION</b>	Low voltage systems Low voltage system mounted
<b>INGRESS PROTECTION</b>	IP20
<b>WEIGHT (KG)</b>	0.3
<b>ADJUSTABILITY</b>	0° to 85° swiveling, 360° rotatable
<b>INFORMATION</b>	REFLECTOR WFL-40° EXCL.LED POWER SUPPLY 48V-DC

### Electrical info

<b>ELECTRICAL</b>	48V-DC
<b>CLASS</b>	III
<b>DIM TYPE</b>	MDL = 1-10V or DALI or push button
<b>ENERGY CLASS</b>	E
<b>CERTIFICATES</b>	CB, ENEC, EPD

### Lightsource info

<b>LIGHTSOURCE NAME</b>	LED
<b>LIGHTSOURCE</b>	LED array 8,6W / CRI>90 (R9: 60) / 2700K / 1041lm
<b>TM-30 VALUES</b>	rf: 89 / Rg: 100
<b>SDCM</b>	SDCM1
<b>RISKGROUPE</b>	RG1
<b>LM80</b>	L90B10 > 50000
<b>BEAMANGLE</b>	40°
<b>LED TECHNICS (LIGHT SOURCE)</b>	1041lm // 8,6W // 121lm/W
<b>LED TECHNICS (LUMINAIRE)</b>	844lm // 9,9W // 85lm/W

### Remarks

Take a look at our **MAGNETIC PROFILES** movie

### Requirements

SPY 39 TUBE or VISOR 39  
LED POWER SUPPLY 48V-DC

### Options

DIMMABLE MODULATOR

# DELTALIGHT

## M26L - SPY 391 92740 MDL


23258 9230 B

For detailed installation instructions, please consult the manual : [23258\\_XXX0\\_HAND.pdf](#)

### FINISH YOUR SPECIFICATION

#### Current supply

#### # of Fixtures

 # of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.

Min current | Max current




**21032 0030** SMART 48 MODULATOR PLUG-IN WD

19

Dimtype: WDL = wireless dimmable

#### SMART 48

#### # of Fixtures

 # of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.

Min current | Max current



**300 90 011** SMART 48 MODULATOR DIM9

19

Dimtype: 1-10V or DALI or push button




**300 90 012** SMART 48 MODULATOR WD

19


Dimtype: WDL = wireless dimmable

#### LED power supplies

#### # of Fixtures

 # of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.

Min current | Max current



**300 89 48 100** LED POWER SUPPLY 48V-DC / 100W DIN


10

Dimtype: non-dimmable

# DELTALIGHT

## M26L - SPY 391 92740 MDL


23258 9230 B



**300 89 48 240** LED POWER SUPPLY 48V-DC / 240W DIN

24

Dimtype: non-dimmable




**21012 0230** LED POWER SUPPLY 48V-DC / 100W

10

Dimtype: non-dimmable

Cutout dimension (mm): 40




**21012 0240** LED POWER SUPPLY 48V-DC / 200W

20

Dimtype: non-dimmable

Cutout dimension (mm): 40

### Light altering devices



**24144 0030 B** VISOR 39 B

### Finish your product



**24144 0010 B** SPY 39 TUBE B

**24144 0010 FBR** SPY 39 TUBE FBR

**24144 0010 FC** SPY 39 TUBE FC

**24144 0010 GC** SPY 39 TUBE GC

**24144 0010 W** SPY 39 TUBE W



**24144 0070** SPY 39 TUBE SBL

# DELTALIGHT


## M26L - SPY 391 92740 MDL

23258 9230 B


### COMPATIBLE COMPOSABLES

#### SHIFTLINE M26L FLOOR

#### Available Colours



**29321 0010** SLM26L F MDL




**29322 002W** SLM26L F MDL WD




#### SHIFTLINE M26L profile (+ SHIFTLINE M26L MATRIX)


#### Available Colours




**23358 0000** SLM26L - PROFILE



**23358 0010** SLM26L - PROFILE 1m



**23358 0020** SLM26L - PROFILE 2m




**23358 0030** SLM26L - PROFILE 3m




#### SHIFTLINE M35R profile


#### Available Colours



**23375 0000** SLM35R - PROFILE



**23375 0010** SLM35R - PROFILE 1m




**23375 0020** SLM35R - PROFILE 2m



# DELTALIGHT

## M26L - SPY 391 92740 MDL

23258 9230 B



**23375 0030** SLM35R - PROFILE 3m



Notes: