





M26L - SPY 391 92740 MDL FG

23258 9230 FG

AVAILABLE IN

BLACK 23258 9230 B
BRUSHED ALU 23258 9230 BRA
BRUSHED ANTHRACITE 23258 9230 BRAT
BRUSHED COPPER 23258 9230 BRCU
BRUSHED GOLD 23258 9230 BRG
BRUSHED OLD BRONZE 23258 9230 BROB
FLEMISH BRONZE 23258 9230 FBR
FLEMISH GOLD 23258 9230 FG
GOLD COLOURED 23258 9230 GC
PIANO BLACK 23258 9230 PB
WHITE 23258 9230 W



[View on website](#)

General info

| | |
|---------------------------|---|
| LOCATION | indoor |
| INSTALLATION | Low voltage systems Low voltage system mounted |
| INGRESS PROTECTION | IP20 |
| WEIGHT (KG) | 0.3 |
| ADJUSTABILITY | 0° to 85° swiveling, 360° rotatable |
| INFORMATION | REFLECTOR WFL-40° EXCL.LED POWER SUPPLY 48V-DC |

Electrical info

| | |
|---------------------|------------------------------------|
| ELECTRICAL | 48V-DC |
| CLASS | III |
| DIM TYPE | MDL = 1-10V or DALI or push button |
| ENERGY CLASS | E |
| CERTIFICATES | ENEC, LCA |

Lightsource info

| | |
|------------------------------------|---|
| LIGHTSOURCE NAME | LED |
| LIGHTSOURCE | LED array 8,6W / CRI>90 (R9: 60) / 2700K / 1041lm |
| TM-30 VALUES | Rf: 89 / Rg: 100 |
| SDCM | SDCM1 |
| RISKGROUP | RG1 |
| LM80 | L90B10 > 50000 |
| LED TECHNICS (LIGHT SOURCE) | 1041lm // 8,6W // 121lm/W |
| LED TECHNICS (LUMINAIRE) | 844lm // 10W // 85lm/W |

Remarks

[Take a look at our MAGNETIC PROFILES movie](#)

M26L - SPY 391 92740 MDL FG

23258 9230 FG

Requirements

SPY 39 TUBE or VISOR 39
LED POWER SUPPLY 48V-DC

Options

DIMMABLE MODULATOR

For detailed installation instructions, please consult the manual: [**23258_XXX0_HAND.pdf**](#)

M26L - SPY 391 92740 MDL FG
 23258 9230 FG

FINISH YOUR SPECIFICATION

Current supply
 #



21032 0030 SMART 48 MODULATOR PLUG-IN WD

19
 ☐

SMART 48
 #



300 90 011 SMART 48 MODULATOR DIM9


19
 ☐



300 90 012 SMART 48 MODULATOR WD


19
 ☐

LED power supplies
 #




300 89 48 100 LED POWER SUPPLY 48V-DC / 100W DIN

10
 ☐



300 89 48 240 LED POWER SUPPLY 48V-DC / 240W DIN

24
 ☐



21012 0230 LED POWER SUPPLY 48V-DC / 100W

10
 ☐



21012 0240 LED POWER SUPPLY 48V-DC / 200W

20
 ☐

M26L - SPY 391 92740 MDL FG
 23258 9230 FG

Light altering devices



24144 0030 B

VISOR 39 B

☐

Finish your product



24144 0010 B

SPY 39 TUBE B

☐

24144 0010 FBR

SPY 39 TUBE FBR

☐

24144 0010 FG

SPY 39 TUBE FG

☐

24144 0010 GC

SPY 39 TUBE GC

☐

24144 0010 W

SPY 39 TUBE W

☐



24144 0070





SPY 39 TUBE SBL

☐

















M26L - SPY 391 92740 MDL FG
23258 9230 FG

COMPATIBLE COMPOSABLES

SHIFTLINE M26L FLOOR Available Colours

| | | |
|---|-----------------------------------|---|
|  | 29321 0010 SLM26L F MDL |  |
|  | 29322 002W SLM26L F MDL WD |  |

SHIFTLINE M26L profile (+ SHIFTLINE M26L MATRIX) Available Colours

| | | |
|---|---------------------------------------|---|
|  | 23358 0000 SLM26L - PROFILE |   |
|  | 23358 0010 SLM26L - PROFILE 1m |   |
|  | 23358 0020 SLM26L - PROFILE 2m |     |
|  | 23358 0030 SLM26L - PROFILE 3m |     |

Notes: