





M26L - SPY 52 92745 DIM5 B

23275 9235 B

AVAILABLE IN
BLACK 23275 9235 B
FLEMISH BRONZE 23275 9235 FBR
FLEMISH GOLD 23275 9235 FG
GOLD COLOURED 23275 9235 GC
WHITE 23275 9235 W



[View on website](#)

General info

LOCATION	indoor
INSTALLATION	Low voltage systems Low voltage system mounted
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.4
ADJUSTABILITY	0° to 90° swiveling, 360° rotatable
INFORMATION	REFLECTOR WFL-45° EXCL.LED POWER SUPPLY 48V-DC Optional REFLECTORS 20° & 30° available

Electrical info

ELECTRICAL	48V-DC
CLASS	III
DIM TYPE	DALI
ENERGY CLASS	E
CERTIFICATES	ENEC, LCA

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 12,4W / CRI>90 (R9: 60) / 2700K / 1403lm
TM-30 VALUES	rf: 89 / Rg: 100
SDCM	SDCM1
RISKGROUP	RG1
LM80	L90B10 > 50000
LED TECHNICS (LIGHT SOURCE)	1403lm // 12,4W // 113lm/W
LED TECHNICS (LUMINAIRE)	898lm // 14W // 63lm/W

Remarks

Take a look at our [MAGNETIC PROFILES movie](#)

Requirements

SPY 52 TUBE
LED POWER SUPPLY 48V-DC

M26L - SPY 52 92745 DIM5 B

23275 9235 B

Accessories

HONEYCOMB 42

SPREAD LENS 42

LINEAR SPREAD LENS 42





SOFTENING LENS 42

GLASS SBL 42







For detailed installation instructions, please consult the manual: [23275_XXX5_HAND.pdf](#)

M26L - SPY 52 92745 DIM5 B
23275 9235 B

FINISH YOUR SPECIFICATION

LED power supplies		#
 <p>55 100 90</p>	300 89 48 100 LED POWER SUPPLY 48V-DC / 100W DIN	7 <input type="checkbox"/>
 <p>63 114 125</p>	300 89 48 240 LED POWER SUPPLY 48V-DC / 240W DIN	16 <input type="checkbox"/>
 <p>17 298 30</p>	21012 0230 LED POWER SUPPLY 48V-DC / 100W	7 <input type="checkbox"/>
 <p>22 392 30</p>	21012 0240 LED POWER SUPPLY 48V-DC / 200W	14 <input type="checkbox"/>

Light altering devices

	<div><div>13</div><div>19810 0010 B</div></div>	HONEYCOMB 42 SINGLE USE B	<input type="checkbox"/>
	<div><div>13</div><div>19810 0020</div></div>	LINEAR SPREAD LENS 42	<input type="checkbox"/>
	<div><div>13</div><div>19810 0030</div></div>	SPREAD LENS 42	<input type="checkbox"/>
	<div><div>13</div><div>19810 0040</div></div>	SOFTENING LENS 42	<input type="checkbox"/>
	<div><div>13</div><div>19810 0050</div></div>	GLASS SBL 42	<input type="checkbox"/>
	<div><div>14</div><div>19810 0060 B</div></div>	HONEYCOMB 42 DOUBLE USE B	<input type="checkbox"/>

M26L - SPY 52 92745 DIM5 B

23275 9235 B

Finish your product



19810 0100 B SPY 52 TUBE B

☐

19810 0100 FBR SPY 52 TUBE FBR

☐

19810 0100 FG SPY 52 TUBE FG

☐


19810 0100 GC SPY 52 TUBE GC

☐


19810 0100 W SPY 52 TUBE W

☐


Replaceable reflector / lens



19810 0180 SPY 52 REFLECTOR 20°

☐


19810 0190 SPY 52 REFLECTOR 45°

☐










19810 0240 SPY 52 REFLECTOR 30°

☐

M26L - SPY 52 92745 DIM5 B
 23275 9235 B

COMPATIBLE COMPOSABLES

SHIFTLINE M26L profile (+ SHIFTLINE M26L MATRIX)	Available Colours
--	-------------------

 <div> <div>32</div> <div>23358 0000 SLM26L - PROFILE</div> </div>	
 <div> <div>32</div> <div>23358 0010 SLM26L - PROFILE 1m</div> </div>	
 <div> <div>32</div> <div>23358 0020 SLM26L - PROFILE 2m</div> </div>	
 <div> <div>32</div> <div>23358 0030 SLM26L - PROFILE 3m</div> </div>	

Notes: