





M20/M26H - SPY 391 92740 MDL W 23315 9230 W

AVAILABLE IN
BLACK 23315 9230 B
BRUSHED ALU 23315 9230 BRA
BRUSHED ANTHRACITE 23315 9230 BRAT
BRUSHED COPPER 23315 9230 BRCU
BRUSHED GOLD 23315 9230 BRG
BRUSHED OLD BRONZE 23315 9230 BROB
FLEMISH BRONZE 23315 9230 FBR
FLEMISH GOLD 23315 9230 FG
GOLD COLOURED 23315 9230 GC
PIANO BLACK 23315 9230 PB
WHITE 23315 9230 W



[View on website](#)

General info

| | |
|---------------------------|---|
| LOCATION | indoor |
| INSTALLATION | Low voltage systems Low voltage system mounted |
| INGRESS PROTECTION | IP20 |
| WEIGHT (KG) | 0.3 |
| ADJUSTABILITY | 0° to 85° swiveling, 355° rotatable |
| INFORMATION | REFLECTOR WFL-40° EXCL.LED POWER SUPPLY 48V-DC |

Electrical info

| | |
|---------------------|------------------------------------|
| ELECTRICAL | 48V-DC |
| CLASS | III |
| DIM TYPE | MDL = 1-10V or DALI or push button |
| ENERGY CLASS | E |
| CERTIFICATES | ENEC, LCA |

Lightsource info

| | |
|------------------------------------|---|
| LIGHTSOURCE NAME | LED |
| LIGHTSOURCE | LED array 8,6W / CRI>90 (R9: 60) / 2700K / 1041lm |
| TM-30 VALUES | rf: 89 / Rg: 100 |
| SDCM | SDCM1 |
| RISKGROUP | RG1 |
| LM80 | L90B10 > 50000 |
| LED TECHNICS (LIGHT SOURCE) | 1041lm // 8,6W // 121lm/W |
| LED TECHNICS (LUMINAIRE) | 844lm // 10W // 85lm/W |

Remarks

[Take a look at our MAGNETIC PROFILES movie](#)



M20/M26H - SPY 391 92740 MDL W

23315 9230 W

Requirements

SPY 39 TUBE or VISOR 39
LED POWER SUPPLY 48V-DC

Options

DIMMABLE MODULATOR

For detailed installation instructions, please consult the manual: [**23315_XXX0_HAND.pdf**](#)

M20/M26H - SPY 391 92740 MDL W
23315 9230 W

FINISH YOUR SPECIFICATION

Current supply#



21032 0030 SMART 48 MODULATOR PLUG-IN WD

19☐

SMART 48#



300 90 011 SMART 48 MODULATOR DIM9


19☐



300 90 012 SMART 48 MODULATOR WD


19☐

LED power supplies#




300 89 48 100 LED POWER SUPPLY 48V-DC / 100W DIN

10☐



300 89 48 240 LED POWER SUPPLY 48V-DC / 240W DIN

24☐



21012 0230 LED POWER SUPPLY 48V-DC / 100W

10☐



21012 0240 LED POWER SUPPLY 48V-DC / 200W

20☐

✕ DELTALIGHT®

M20/M26H - SPY 391 92740 MDL W

23315 9230 W

Light altering devices



24144 0030 B VISOR 39 B

☐

Finish your product



24144 0010 B SPY 39 TUBE B

☐

24144 0010 FBR SPY 39 TUBE FBR

☐

24144 0010 FG SPY 39 TUBE FG

☐

24144 0010 GC SPY 39 TUBE GC

☐

24144 0010 W SPY 39 TUBE W

☐



24144 0070 SPY 39 TUBE SBL


☐

M20/M26H - SPY 391 92740 MDL W
23315 9230 W


COMPATIBLE COMPOSABLES

SHIFTLINE M26H FLOOR

Available Colours



29323 920W SLM26H F MDL WD




29323 930W SLM26H F MDL WD




SHIFTLINE M26H profile


Available Colours




23359 0000 SLM26H - PROFILE



23359 0010 SLM26H - PROFILE 1m



23359 0020 SLM26H - PROFILE 2m



23359 0030 SLM26H - PROFILE 3m



SPLITLINE M20 ST profile

Available Colours



23397 0000 SPM20 ST - PROFILE











23397 0020 SPM20 ST - PROFILE 2m



23397 0030 SPM20 ST - PROFILE 3m



M20/M26H - SPY 391 92740 MDL W
23315 9230 W

| SPLITLINE M20 profile | | Available Colours |
|---|--|---|
|  | 420 20 10 00 SPM20 - PROFILE 1m |  |
|  | 420 20 20 00 SPM20 - PROFILE 2m |  |
|  | 420 20 30 00 SPM20 - PROFILE 3m |  |
|  | 23301 0000 SPM20 - PROFILE B |  |

Notes: