



## M20/M26H - SPY 391 93040 MDL

23315 9330 B

AVAILABLE IN

**BLACK** 23315 9330 B

**BRUSHED ALU** 23315 9330 BRA

**BRUSHED ANTHRACITE** 23315 9330 BRAT

**BRUSHED COPPER** 23315 9330 BRCU

**BRUSHED GOLD** 23315 9330 BRG

**BRUSHED OLD BRONZE** 23315 9330 BROB



**FLEMISH BRONZE** 23315 9330 FBR

**FLEMISH GOLD** 23315 9330 FG

**GOLD COLOURED** 23315 9330 GC

**PIANO BLACK** 23315 9330 PB

**WHITE** 23315 9330 W



[View on website](#)



General info	
<b>LOCATION</b>	indoor
<b>INSTALLATION</b>	Low voltage systems Low voltage system mounted
<b>INGRESS PROTECTION</b>	IP20
<b>WEIGHT (KG)</b>	0.3
<b>ADJUSTABILITY</b>	0° to 85° swiveling, 355° rotatable
<b>INFORMATION</b>	REFLECTOR WFL-40° EXCL.LED POWER SUPPLY 48V-DC
Electrical info	
<b>ELECTRICAL</b>	48V-DC
<b>CLASS</b>	III
<b>DIM TYPE</b>	MDL = 1-10V or DALI or push button
<b>ENERGY CLASS</b>	D
<b>CERTIFICATES</b>	CB, ENEC, EPD
Lightsource info	
<b>LIGHTSOURCE NAME</b>	LED
<b>LIGHTSOURCE</b>	LED array 8,6W / CRI>90 (R9: 52) / 3000K / 1089lm
<b>TM-30 VALUES</b>	rf: 90 / Rg: 99
<b>SDCM</b>	SDCM1
<b>RISKGROUP</b>	RG1
<b>LM80</b>	L90B10 > 50000
<b>BEAMANGLE</b>	40°
<b>LED TECHNICS (LIGHT SOURCE)</b>	1089lm // 8,6W // 127lm/W
<b>LED TECHNICS (LUMINAIRE)</b>	883lm // 9,9W // 89lm/W

### Remarks

Take a look at our **MAGNETIC PROFILES** movie

### Requirements

SPY 39 TUBE or VISOR 39

LED POWER SUPPLY 48V-DC

### Options

DIMMABLE MODULATOR

# DELTALIGHT

## M20/M26H - SPY 391 93040 MDL


23315 9330 B

For detailed installation instructions, please consult the manual : [23315\\_XXX0\\_HAND.pdf](#)


### FINISH YOUR SPECIFICATION

#### Current supply

#### # of Fixtures

 # of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.

Min current | Max current




**21032 0030** SMART 48 MODULATOR PLUG-IN WD

19

Dimtype: WDL = wireless dimmable

#### SMART 48

#### # of Fixtures

 # of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.

Min current | Max current



**300 90 011** SMART 48 MODULATOR DIM9

19

Dimtype: 1-10V or DALI or push button




**300 90 012** SMART 48 MODULATOR WD

19


Dimtype: WDL = wireless dimmable

#### LED power supplies

#### # of Fixtures

 # of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.

Min current | Max current



**300 89 48 100** LED POWER SUPPLY 48V-DC / 100W DIN

10

Dimtype: non-dimmable

# DELTALIGHT

## M20/M26H - SPY 391 93040 MDL

23315 9330 B



**300 89 48 240** LED POWER SUPPLY 48V-DC / 240W DIN

24

Dimtype: non-dimmable




**21012 0230** LED POWER SUPPLY 48V-DC / 100W

10

Dimtype: non-dimmable

Cutout dimension (mm): 40




**21012 0240** LED POWER SUPPLY 48V-DC / 200W

20

Dimtype: non-dimmable


Cutout dimension (mm): 40

### Light altering devices



**24144 0030 B** VISOR 39 B

### Finish your product



**24144 0010 B** SPY 39 TUBE B

**24144 0010 FBR** SPY 39 TUBE FBR

**24144 0010 FC** SPY 39 TUBE FC

**24144 0010 GC** SPY 39 TUBE GC

**24144 0010 W** SPY 39 TUBE W



**24144 0070** SPY 39 TUBE SBL

# DELTALIGHT


## M20/M26H - SPY 391 93040 MDL

23315 9330 B


### COMPATIBLE COMPOSABLES

#### SHIFTLINE M26H FLOOR

#### Available Colours



**29323 920W** SLM26H F MDL WD




**29323 930W** SLM26H F MDL WD




#### SHIFTLINE M26H profile


#### Available Colours




**23359 0000** SLM26H - PROFILE



**23359 0010** SLM26H - PROFILE 1m



**23359 0020** SLM26H - PROFILE 2m



**23359 0030** SLM26H - PROFILE 3m



#### SPLITLINE M20 ST profile

#### Available Colours



**23397 0000** SPM20 ST - PROFILE



**23397 0020** SPM20 ST - PROFILE 2m



**23397 0030** SPM20 ST - PROFILE 3m




# DELTALIGHT

## M20/M26H - SPY 391 93040 MDL


23315 9330 B

### SPLITLINE M20 profile


### Available Colours




**420 20 10 00** SPM20 - PROFILE 1m



**420 20 20 00** SPM20 - PROFILE 2m



**420 20 30 00** SPM20 - PROFILE 3m



**23301 0000** SPM20 - PROFILE B



Notes: