



## M20/M26H - SPY 391 92740 DIM5

23316 9235 BRAT

AVAILABLE IN

**BLACK** 23316 9235 B

**BRUSHED ALU** 23316 9235 BRA

**BRUSHED ANTHRACITE** 23316 9235 BRAT

**BRUSHED COPPER** 23316 9235 BRCU

**BRUSHED GOLD** 23316 9235 BRG

**BRUSHED OLD BRONZE** 23316 9235 BROB



**FLEMISH BRONZE** 23316 9235 FBR

**FLEMISH GOLD** 23316 9235 FG

**GOLD COLOURED** 23316 9235 GC

**PIANO BLACK** 23316 9235 PB

**WHITE** 23316 9235 W



[View on website](#)



### General info

<b>LOCATION</b>	indoor
<b>INSTALLATION</b>	Low voltage systems Low voltage system mounted
<b>INGRESS PROTECTION</b>	IP20
<b>WEIGHT (KG)</b>	0.3
<b>ADJUSTABILITY</b>	0° to 85° swiveling, 355° rotatable
<b>INFORMATION</b>	REFLECTOR WFL-40° EXCL.LED POWER SUPPLY 48V-DC

### Electrical info

<b>ELECTRICAL</b>	48V-DC
<b>CLASS</b>	III
<b>DIM TYPE</b>	DALI
<b>ENERGY CLASS</b>	E
<b>CERTIFICATES</b>	CB, ENEC, EPD

### Lightsource info

<b>LIGHTSOURCE NAME</b>	LED
<b>LIGHTSOURCE</b>	LED array 8,6W / CRI>90 (R9: 60) / 2700K / 1041lm
<b>TM-30 VALUES</b>	rf: 89 / Rg: 100
<b>SDCM</b>	SDCM1
<b>RISKGROUP</b>	RG1
<b>LM80</b>	L90B10 > 50000
<b>BEAMANGLE</b>	40°
<b>LED TECHNICS (LIGHT SOURCE)</b>	1041lm // 8,6W // 121lm/W
<b>LED TECHNICS (LUMINAIRE)</b>	844lm // 9,9W // 85lm/W

### Remarks

Take a look at our **MAGNETIC PROFILES** movie

### Requirements

SPY 39 TUBE or VISOR 39

LED POWER SUPPLY 48V-DC

# DELTALIGHT

## M20/M26H - SPY 391 92740 DIM5


23316 9235 BRAT

For detailed installation instructions, please consult the manual : [23316\\_XXX5\\_HAND.pdf](#)


### FINISH YOUR SPECIFICATION

#### LED power supplies

#### # of Fixtures

 # of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.


Min current | Max current



**300 89 48 100** LED POWER SUPPLY 48V-DC / 100W DIN

10


Dimtype: non-dimmable



**300 89 48 240** LED POWER SUPPLY 48V-DC / 240W DIN

24

Dimtype: non-dimmable




**21012 0230** LED POWER SUPPLY 48V-DC / 100W

10

Dimtype: non-dimmable

Cutout dimension (mm): 40




**21012 0240** LED POWER SUPPLY 48V-DC / 200W

20

Dimtype: non-dimmable

Cutout dimension (mm): 40

#### Light altering devices



**24144 0030 B** VISOR 39 B

# DELTALIGHT

## M20/M26H - SPY 391 92740 DIM5

23316 9235 BRAT

### Finish your product



**24144 0010 B** SPY 39 TUBE B

**24144 0010 FBR** SPY 39 TUBE FBR

**24144 0010 FG** SPY 39 TUBE FG

**24144 0010 GC** SPY 39 TUBE GC

**24144 0010 W** SPY 39 TUBE W



**24144 0070** SPY 39 TUBE SBL

## COMPATIBLE COMPOSABLES

### SHIFTLINE M26H + SBL

### Available Colours



**30411 9205** SHIFTLINE M26H + SBL 2m DIM5



**30411 9305** SHIFTLINE M26H + SBL 2m DIM5



**30412 9205** SHIFTLINE M26H + SBL 3m DIM5




**30412 9305** SHIFTLINE M26H + SBL 3m DIM5



# DELTALIGHT

## M20/M26H - SPY 391 92740 DIM5

23316 9235 BRAT



**30413 9205** SHIFTLINE M26H + SBL 4m DIM5




**30413 9305** SHIFTLINE M26H + SBL 4m DIM5



### SHIFTLINE M26H profile


### Available Colours




**23359 0000** SLM26H - PROFILE



**23359 0010** SLM26H - PROFILE 1m



**23359 0020** SLM26H - PROFILE 2m



**23359 0030** SLM26H - PROFILE 3m



### SPLITLINE M20 ST profile

### Available Colours



**23397 0000** SPM20 ST - PROFILE



**23397 0020** SPM20 ST - PROFILE 2m



**23397 0030** SPM20 ST - PROFILE 3m




# DELTALIGHT

## M20/M26H - SPY 391 92740 DIM5


23316 9235 BRAT

### SPLITLINE M20 profile


### Available Colours




**420 20 10 00** SPM20 - PROFILE 1m



**420 20 20 00** SPM20 - PROFILE 2m



**420 20 30 00** SPM20 - PROFILE 3m



**23301 0000** SPM20 - PROFILE B



Notes: