





M - DOT.COM M4 92732 DIM5 B-B
23355 9225 B-B

AVAILABLE IN
BLACK-BLACK 23355 9225 B-B
BLACK-CHROMED 23355 9225 B-C
BLACK-GOLD MATT 23355 9225 B-MMAT



 [View on website](#)

General info

LOCATION	indoor
INSTALLATION	Low voltage systems Low voltage system mounted
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.2
ADJUSTABILITY	non adjustable
INFORMATION	4 x REFLECTOR FL-32° EXCL.LED POWER SUPPLY 48V-DC

Electrical info

ELECTRICAL	48V-DC
CLASS	III
DIM TYPE	DALI
ENERGY CLASS	E
CERTIFICATES	CB, ENEC

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED cluster 5,7W / CRI>90 (R9: 50) / 2700K / 631lm
TM-30 VALUES	Rf: 92 / Rg: 100
SDCM	SDCM3
RISKGROUP	RG2
LM80	L80 > 60000
LED TECHNICS (LIGHT SOURCE)	631lm // 5,7W // 111lm/W
LED TECHNICS (LUMINAIRE)	462lm // 7W // 70lm/W

Remarks

Take a look at our [MAGNETIC PROFILES](#) movie





Requirements

LED POWER SUPPLY 48V-DC

M - DOT.COM M4 92732 DIM5 B-B
 23355 9225 B-B



















For detailed installation instructions, please consult the manual: [23355_XXX5_HAND.pdf](#)

FINISH YOUR SPECIFICATION

LED power supplies		#
	300 89 48 100 LED POWER SUPPLY 48V-DC / 100W DIN	15 <input type="checkbox"/>
	300 89 48 240 LED POWER SUPPLY 48V-DC / 240W DIN	37 <input type="checkbox"/>
	21012 0230 LED POWER SUPPLY 48V-DC / 100W	15 <input type="checkbox"/>
	21012 0240 LED POWER SUPPLY 48V-DC / 200W	31 <input type="checkbox"/>

















M - DOT.COM M4 92732 DIM5 B-B
23355 9225 B-B

COMPATIBLE COMPOSABLES

















SHIFTLINE M26H + SBL		Available Colours
	30411 9205 SHIFTLINE M26H + SBL 2m DIM5	 
	30411 9305 SHIFTLINE M26H + SBL 2m DIM5	 
	30412 9205 SHIFTLINE M26H + SBL 3m DIM5	 
	30412 9305 SHIFTLINE M26H + SBL 3m DIM5	 
	30413 9205 SHIFTLINE M26H + SBL 4m DIM5	 
	30413 9305 SHIFTLINE M26H + SBL 4m DIM5	 

M - DOT.COM M4 92732 DIM5 B-B
23355 9225 B-B









SHIFTLINE M26H profile Available Colours









	23359 0000 SLM26H - PROFILE	 
	23359 0010 SLM26H - PROFILE 1m	 
	23359 0020 SLM26H - PROFILE 2m	   
	23359 0030 SLM26H - PROFILE 3m	   

SHIFTLINE M26L profile (+ SHIFTLINE M26L MATRIX) Available Colours

	23358 0000 SLM26L - PROFILE	 
	23358 0010 SLM26L - PROFILE 1m	 
	23358 0020 SLM26L - PROFILE 2m	   
	23358 0030 SLM26L - PROFILE 3m	   

M - DOT.COM M4 92732 DIM5 B-B
 23355 9225 B-B

SPLITLINE M20 ST profile		Available Colours
	23397 0000 SPM20 ST - PROFILE	 
	23397 0020 SPM20 ST - PROFILE 2m	 
	23397 0030 SPM20 ST - PROFILE 3m	 

SPLITLINE M20 profile		Available Colours
	420 20 10 00 SPM20 - PROFILE 1m	
	420 20 20 00 SPM20 - PROFILE 2m	
	420 20 30 00 SPM20 - PROFILE 3m	
	23301 0000 SPM20 - PROFILE B	

Notes: