



MICROSPY IN 92730

24110 9220 W

AVAILABLE IN
BLACK 24110 9220 B
WHITE 24110 9220 W



 [View on website](#)



General info

LOCATION	indoor
INSTALLATION	Ceiling Recessed
CUTOUT SHAPE/SIZE (MM)	round - 36
RECESSED DEPTH (MM)	75
THICKNESS OF MOUNTING SURFACE (MM)	min.2 - max.25
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.1
ADJUSTABILITY	non adjustable
INFORMATION	LENS FL-30° EXCL.LED POWER SUPPLY 350-450mA-DC

Electrical info

CLASS	III
DIM TYPE	depending on power supply
ENERGY CLASS	F
CERTIFICATES	CB, EAC, ENEC

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 3,9-5,1W / CRI>90 (R9: 56) / 2700K / 385-480lm
TM-30 VALUES	rf: 91 / Rg: 99
SDCM	SDCM2
RISKGROUP	RG2 (threshold 0,6m)
LM80	L90B10 > 41000
BEAMANGLE	30°
LED TECHNICS (LIGHT SOURCE)	480lm // 5,1W // 94lm/W
LED TECHNICS (LUMINAIRE)	376lm // 5,9W // 64lm/W

Requirements

LED POWER SUPPLY 350 / 450mA-DC DIM










For detailed installation instructions, please consult the manual : [24110_XXXX_HAND.pdf](#)

DELTALIGHT




MICROSPY IN 92730

24110 9220 W

CEILING COMPATIBILITY

Ceiling Type	Mounting Kit
 System ceiling	-
 Plasterboard	-
 Stucanet	-
 Wood	-
 Concrete	-
 Concrete + plaster	-
 Lintel + plaster	-
 Hollow-core slab + plaster	-
 Stretched ceiling	-

FINISH YOUR SPECIFICATION

LED power supplies	# of Fixtures
	Min current Max current
<p> # of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the ' ' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.</p>	
 <p>300 48 350 ED1 LED POWER CONVERTER 48V-DC to 350 mA-DC / 15W DIM1</p> <p>Dimtype: 1-10V</p> <p>Cutout dimension (mm): 30</p>	3 <input type="text"/>
 <p>300 48 350 ED5 LED POWER CONVERTER 48V-DC to 350 mA-DC / 15W DIM5</p> <p>Dimtype: DALI</p> <p>Cutout dimension (mm): 45</p>	3 <input type="text"/>

DELTALIGHT

MICROSPY IN 92730

24110 9220 W



300 48 350 MDL LED POWER CONVERTER 48V-DC to 350 mA-DC / 15W MDL

3

Dimtype: non-dimmable

Cutout dimension (mm): 30




300 48 350 WDL LED POWER CONVERTER 48V-DC to 350 mA-DC / 15W WDL

3

Dimtype: WDL = wireless dimmable

Cutout dimension (mm): 45




300 90 61 LED POWER SUPPLY MULTI-POWER DIM6

3 | - | -

Dimtype: mains (phase cut-off) or push button

Cutout dimension (mm): 56




300 90 63 LED POWER SUPPLY MULTI-POWER DIM9

6(6) | -

Dimtype: 1-10V or DALI or push button

Cutout dimension (mm): 82




300 90 64 LED POWER SUPPLY MULTI-POWER DIM7

4(3) | - | -

Dimtype: 1-10V or push button


Cutout dimension (mm): 72



300 90 67 LED POWER CONVERTER 24V-DC TO MULTI CURRENT 48W DIM9

3 | - | -

Dimtype: 1-10V or DALI or push button




300 90 68 LED POWER SUPPLY MULTI-POWER DIM5

3(3) | - | -

Dimtype: DALI

Cutout dimension (mm): 72




300 90 69 LED POWER SUPPLY MULTI-POWER HV DIM9

2->9(10) | 2->9(4)

Dimtype: 1-10V or DALI or push button

Cutout dimension (mm): 84




300 90 91 LED POWER SUPPLY 350mA-DC / 15W

3(2)

Dimtype: non-dimmable

Cutout dimension (mm): 40



300 90 108 LED POWER SUPPLY 350mA-DC / 8W

1


Dimtype: non-dimmable

Cutout dimension (mm): 40

DELTALIGHT

MICROSPY IN 92730

24110 9220 W




300 90 110 LED POWER SUPPLY 350mA-DC / 10W DIM8

2->2

Dimtype: mains (phase cut-off)

Cutout dimension (mm): 42




300 90 116 LED POWER SUPPLY 350mA-DC / 18W DIM8

3->4

Dimtype: mains (phase cut-off)

Cutout dimension (mm): 55




300 90 124 LED POWER SUPPLY MULTI-POWER DIM7

2->4(3) | 3(2)

Dimtype: 1-10V or push button

Cutout dimension (mm): 55




300 90 125 LED POWER SUPPLY MULTI-POWER MINI DIM5

4(3) | 3(2)

Dimtype: DALI

Cutout dimension (mm): 55




300 90 134 LED POWER SUPPLY MULTI-POWER HV DIM7

2->8(8) | - | -

Dimtype: 1-10V or push button

Cutout dimension (mm): 84




300 90 135 LED POWER SUPPLY MULTI-POWER HV

4->6 | - | -

Dimtype: non-dimmable

Cutout dimension (mm): 90




300 90 3112 LED POWER SUPPLY 350mA-DC / 16W DIM8

2->3

Dimtype: mains (phase cut-off)

Cutout dimension (mm): 43




21012 004W LED POWER SUPPLY MULTI-POWER WDL

5(5) | - | -

Dimtype: WDL = wireless dimmable

Cutout dimension (mm): 84




21012 005W LED POWER SUPPLY MULTI-POWER COMPACT WDL

4 | -

Dimtype: WDL = wireless dimmable

Cutout dimension (mm): 54



21012 0298 LED POWER SUPPLY MULTI POWER 250-900 / 20W DIM8

3 | 3


Dimtype: mains (phase cut-off)

Cutout dimension (mm): 48

DELTALIGHT

MICROSPY IN 92730

24110 9220 W




21012 0480 LED POWER SUPPLY 350mA-DC / 17W IP68

4(3)



Dimtype: non-dimmable

Cutout dimension (mm): 60



21032 0295 LED POWER CONVERTER 48V-DC to 350 mA-DC / 15W DIM5

3



Dimtype: DALI

Cutout dimension (mm): 30

Notes: