




## MICROSPY IN TRIMLESS OK 92730

24112 9220 B

AVAILABLE IN  
**BLACK** 24112 9220 B  
**WHITE** 24112 9220 W



 [View on website](#)



### General info

<b>LOCATION</b>	indoor
<b>INSTALLATION</b>	Ceiling Recessed
<b>CUTOUT SHAPE/SIZE (MM)</b>	round - Ø KIT
<b>RECESSED DEPTH (MM)</b>	75
<b>INGRESS PROTECTION</b>	IP20
<b>WEIGHT (KG)</b>	0.1
<b>ADJUSTABILITY</b>	0° to 20° swiveling, 350° rotatable
<b>INFORMATION</b>	LENS FL-30° EXCL.LED POWER SUPPLY 350-450mA-DC

### Electrical info

<b>CLASS</b>	III
<b>DIM TYPE</b>	depending on power supply
<b>ENERGY CLASS</b>	E
<b>CERTIFICATES</b>	CB, ENEC, UL

### Lightsource info

<b>LIGHTSOURCE NAME</b>	LED
<b>LIGHTSOURCE</b>	LED array 3,9-5,1W / CRI>90 (R9: 56) / 2700K / 385-480lm
<b>TM-30 VALUES</b>	rf: 91 / Rg: 99
<b>SDCM</b>	SDCM2
<b>RISKGROUP</b>	RG2 (threshold 0,6m)
<b>LM80</b>	L90B10 > 41000
<b>BEAMANGLE</b>	30°
<b>LED TECHNICS (LIGHT SOURCE)</b>	480lm // 5,1W // 94lm/W
<b>LED TECHNICS (LUMINAIRE)</b>	364lm // 5,9W // 62lm/W

### Requirements

MOUNTING KIT TRIMLESS MICROSPY IN OK  
 LED POWER SUPPLY 350 / 450mA-DC DIM (Remote)

### Accessories

MICRO VISOR













For detailed installation instructions, please consult the manual : [24112\\_XXXX\\_HAND.pdf](#)

# DELTALIGHT

## MICROSPY IN TRIMLESS OK 92730

24112 9220 B

### CEILING COMPATIBILITY

Ceiling Type	Mounting Kit	
 System ceiling	 15212 2020 - MOUNTING KIT TRIMLESS MICROSPY IN OK	Required
 Plasterboard	 15212 2020 - MOUNTING KIT TRIMLESS MICROSPY IN OK	Required
 Stucanet	 15212 2020 - MOUNTING KIT TRIMLESS MICROSPY IN OK	Required
 Concrete + plaster	 15212 2020 - MOUNTING KIT TRIMLESS MICROSPY IN OK	Required
 Lintel + plaster	 15212 2020 - MOUNTING KIT TRIMLESS MICROSPY IN OK	Required
 Hollow-core slab + plaster	 15212 2020 - MOUNTING KIT TRIMLESS MICROSPY IN OK	Required

### FINISH YOUR SPECIFICATION


#### LED power supplies

#### # of Fixtures



# of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.

Min current | Max current




**300 48 350 ED1** LED POWER CONVERTER 48V-DC to 350 mA-DC / 15W DIM1

3

Dimtype: 1-10V

Cutout dimension (mm): 30




**300 48 350 ED5** LED POWER CONVERTER 48V-DC to 350 mA-DC / 15W DIM5

3

Dimtype: DALI

Cutout dimension (mm): 45




**300 48 350 MDL** LED POWER CONVERTER 48V-DC to 350 mA-DC / 15W MDL

3

Dimtype: non-dimmable

Cutout dimension (mm): 30



**300 48 350 WDL** LED POWER CONVERTER 48V-DC to 350 mA-DC / 15W WDL

3


Dimtype: WDL = wireless dimmable

Cutout dimension (mm): 45

# DELTALIGHT

## MICROSPY IN TRIMLESS OK 92730

24112 9220 B




**300 90 61** LED POWER SUPPLY MULTI-POWER DIM6

3 | - | -

**Dimtype: mains (phase cut-off) or push button**

**Cutout dimension (mm): 56**




**300 90 63** LED POWER SUPPLY MULTI-POWER DIM9

6(6) | -

**Dimtype: 1-10V or DALI or push button**

**Cutout dimension (mm): 82**




**300 90 64** LED POWER SUPPLY MULTI-POWER DIM7

4(3) | - | -

**Dimtype: 1-10V or push button**


**Cutout dimension (mm): 72**



**300 90 67** LED POWER CONVERTER 24V-DC TO MULTI CURRENT 48W DIM9

3 | - | -

**Dimtype: 1-10V or DALI or push button**




**300 90 68** LED POWER SUPPLY MULTI-POWER DIM5

3(3) | - | -

**Dimtype: DALI**

**Cutout dimension (mm): 72**




**300 90 69** LED POWER SUPPLY MULTI-POWER HV DIM9

2->9(10) | 2->9(4)

**Dimtype: 1-10V or DALI or push button**

**Cutout dimension (mm): 84**




**300 90 91** LED POWER SUPPLY 350mA-DC / 15W

3(2)

**Dimtype: non-dimmable**

**Cutout dimension (mm): 40**




**300 90 108** LED POWER SUPPLY 350mA-DC / 8W

1

**Dimtype: non-dimmable**

**Cutout dimension (mm): 40**




**300 90 110** LED POWER SUPPLY 350mA-DC / 10W DIM8

2->2

**Dimtype: mains (phase cut-off)**

**Cutout dimension (mm): 42**



**300 90 116** LED POWER SUPPLY 350mA-DC / 18W DIM8

3->4


**Dimtype: mains (phase cut-off)**

**Cutout dimension (mm): 55**

# DELTALIGHT

## MICROSPY IN TRIMLESS OK 92730

24112 9220 B




**300 90 124** LED POWER SUPPLY MULTI-POWER DIM7

2->4(3) | 3(2)



**Dimtype: 1-10V or push button**

**Cutout dimension (mm): 55**




**300 90 125** LED POWER SUPPLY MULTI-POWER MINI DIM5

4(3) | 3(2)



**Dimtype: DALI**

**Cutout dimension (mm): 55**




**300 90 134** LED POWER SUPPLY MULTI-POWER HV DIM7

2->8(8) | - | -



**Dimtype: 1-10V or push button**

**Cutout dimension (mm): 84**




**300 90 135** LED POWER SUPPLY MULTI-POWER HV

4->6 | - | -



**Dimtype: non-dimmable**

**Cutout dimension (mm): 90**




**300 90 3112** LED POWER SUPPLY 350mA-DC / 16W DIM8

2->3



**Dimtype: mains (phase cut-off)**

**Cutout dimension (mm): 43**




**21012 004W** LED POWER SUPPLY MULTI-POWER WDL

5(5) | - | -



**Dimtype: WDL = wireless dimmable**

**Cutout dimension (mm): 84**




**21012 005W** LED POWER SUPPLY MULTI-POWER COMPACT WDL

4 | -



**Dimtype: WDL = wireless dimmable**

**Cutout dimension (mm): 54**




**21012 0298** LED POWER SUPPLY MULTI POWER 250-900 / 20W DIM8

3 | 3



**Dimtype: mains (phase cut-off)**

**Cutout dimension (mm): 48**




**21012 0480** LED POWER SUPPLY 350mA-DC / 17W IP68

4(3)



**Dimtype: non-dimmable**

**Cutout dimension (mm): 60**



**21032 0295** LED POWER CONVERTER 48V-DC to 350 mA-DC / 15W DIM5

3



**Dimtype: DALI**

**Cutout dimension (mm): 30**


# DELTALIGHT

## MICROSPY IN TRIMLESS OK 92730

24112 9220 B

### Mounting kits

---




**15212 2020** MOUNTING KIT TRIMLESS MICROSPY IN OK



Cutout dimension (mm): 68

### Light altering devices

---



**10034 0010 B** MICRO VISOR B



Notes: