





## SPY 39 L ON 2 93040 DIM8 B-B

24140 9338 B-B

AVAILABLE IN

**BLACK-BLACK** 24140 9338 B-B

**WHITE-WHITE** 24140 9338 W-W



[View on website](#)

### General info

<b>LOCATION</b>	indoor
<b>INSTALLATION</b>	Ceiling Surface mounted
<b>INGRESS PROTECTION</b>	IP20
<b>WEIGHT (KG)</b>	0.7
<b>ADJUSTABILITY</b>	0° to 85° swiveling, 355° rotatable
<b>INFORMATION</b>	REFLECTOR WFL-40° INCL.DIMMABLE LED POWER SUPPLY 350/500mA-DC Current selection via jumper on power supply

### Electrical info

<b>ELECTRICAL</b>	220-240V / 50-60Hz
<b>CLASS</b>	I
<b>POWER SUPPLY INCLUDED</b>	YES
<b>DIM TYPE</b>	mains (phase cut-off)
<b>ENERGY CLASS</b>	D

### Lightsource info

<b>LIGHTSOURCE NAME</b>	LED
<b>LIGHTSOURCE</b>	2 x (LED array 8,6W / CRI>90 (R9: 52) / 3000K / 1089lm)
<b>TM-30 VALUES</b>	Rf: 90 / Rg: 99
<b>SDCM</b>	SDCM1
<b>RISKGROUP</b>	RG1
<b>LM80</b>	L90B10 > 50000
<b>LED TECHNICS (LIGHT SOURCE)</b>	2178lm // 17,2W // 127lm/W
<b>LED TECHNICS (LUMINAIRE)</b>	1475lm // 20W // 75lm/W

### Requirements

SPY 39 LTUBE

For detailed installation instructions, please consult the manual: [24140\\_XXX8\\_HAND.pdf](#)

SPY 39 L ON 2 93040 DIM8 B-B

24140 9338 B-B

FINISH YOUR SPECIFICATION

Finish your product

	<b><u>24144 0020 B</u></b>	SPY 39 L TUBE B	<input type="checkbox"/>
	<b><u>24144 0020 FBR</u></b>	SPY 39 L TUBE FBR	<input type="checkbox"/>
	<b><u>24144 0020 FG</u></b>	SPY 39 L TUBE FG	<input type="checkbox"/>
	<b><u>24144 0020 GC</u></b>	SPY 39 L TUBE GC	<input type="checkbox"/>
	<b><u>24144 0020 W</u></b>	SPY 39 L TUBE W	<input type="checkbox"/>

Notes: