





SPY 39 L ON 2 93040 DIM8 B-B

24140 9338 B-B

AVAILABLE IN

BLACK-BLACK 24140 9338 B-B

WHITE-WHITE 24140 9338 W-W



[View on website](#)

General info

LOCATION	indoor
INSTALLATION	Ceiling Surface mounted
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.7
ADJUSTABILITY	0° to 85° swiveling, 355° rotatable
INFORMATION	REFLECTOR WFL-40° INCL.DIMMABLE LED POWER SUPPLY 350/500mA-DC Current selection via jumper on power supply

Electrical info

ELECTRICAL	220-240V / 50-60Hz
CLASS	I
POWER SUPPLY	YES
DIM TYPE	mains (phase cut-off)
ENERGY CLASS	D

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	2 x (LED array 8,6W / CRI>90 (R9: 52) / 3000K / 1089lm)
TM-30 VALUES	rf: 90 / Rg: 99
SDCM	SDCM1
RISKGROUPE	RG1
LM80	L90B10 > 50000
LED TECHNICS (LIGHT SOURCE)	2178lm // 17,2W // 127lm/W
LED TECHNICS (LUMINAIRE)	1475lm // 20W // 75lm/W

Requirements

SPY 39 LTUBE

For detailed installation instructions, please consult the manual: [24140_XXX8_HAND.pdf](#)

SPY 39 L ON 2 93040 DIM8 B-B

24140 9338 B-B

FINISH YOUR SPECIFICATION

Finish your product

	<u>24144 0020 B</u>	SPY 39 L TUBE B	<input type="checkbox"/>
	<u>24144 0020 FBR</u>	SPY 39 L TUBE FBR	<input type="checkbox"/>
	<u>24144 0020 FG</u>	SPY 39 L TUBE FG	<input type="checkbox"/>
	<u>24144 0020 GC</u>	SPY 39 L TUBE GC	<input type="checkbox"/>
	<u>24144 0020 W</u>	SPY 39 L TUBE W	<input type="checkbox"/>

Notes: