



## BOXY L+ 93033 DIM8



251 67 811 932 ED8 W-W

AVAILABLE IN

**ALU GREY-ALU GREY** 251 67 811 932 ED8 A-A

**BLACK-BLACK** 251 67 811 932 ED8 B-B

**WHITE-WHITE** 251 67 811 932 ED8 W-W



[View on website](#)



### General info

<b>LOCATION</b>	indoor-outdoor
<b>INSTALLATION</b>	Ceiling Surface mounted
<b>INGRESS PROTECTION</b>	IP53
<b>PROTECTION AGAINST MECHANICAL IMPACT</b>	IK03
<b>WEIGHT (KG)</b>	0.5
<b>ADJUSTABILITY</b>	non adjustable
<b>INFORMATION</b>	REFLECTOR FL-33° INCL.DIMMABLE POWER SUPPLY 350mA-DC

### Electrical info

<b>ELECTRICAL</b>	220-240V / 50-60Hz
<b>CLASS</b>	II
<b>POWER SUPPLY</b>	YES
<b>DIM TYPE</b>	mains (phase cut-off)
<b>ENERGY CLASS</b>	C
<b>CERTIFICATES</b>	CB, EAC, ENEC, LCA, RCM

### Lightsource info

<b>LIGHTSOURCE NAME</b>	LED
<b>LIGHTSOURCE</b>	LED array 5,8W / CRI>90 (R9: 52) / 3000K / 787lm
<b>TM-30 VALUES</b>	rf: 90 / Rg: 99
<b>SDCM</b>	SDCM1
<b>RISKGROUP</b>	RG1
<b>LM80</b>	L90B10 > 50000
<b>BEAMANGLE</b>	33°
<b>LED TECHNICS (LIGHT SOURCE)</b>	787lm // 5,8W // 135lm/W
<b>LED TECHNICS (LUMINAIRE)</b>	628lm // 6,7W // 94lm/W

For detailed installation instructions, please consult the manual : [251\\_67\\_811\\_XXX\\_ED8\\_HAND.pdf](#)


# DELTALIGHT

## BOXY L+ 93033 DIM8

251 67 811 932 ED8 W-W

### FINISH YOUR SPECIFICATION

#### Miscellaneous control equipment



**300 90 004 ED8** WIRELESS CONTROL DIM8

Dimtype: WDL = wireless dimmable

Cutout dimension (mm): 40

#### Light altering devices



Ø40



Ø45

**251 70 03 01 B** BOXY HONEYCOMB B

**251 70 03 01 W** BOXY HONEYCOMB W



Ø40



Ø45

**251 70 03 04 B** BOXY SOFTENING LENS B

**251 70 03 04 W** BOXY SOFTENING LENS W



Ø40



Ø45

**251 70 03 05 B** BOXY GLASS SBL B

**251 70 03 05 W** BOXY GLASS SBL W

Notes: