





BOXY L+ 93033 DIM8 W-W

251 67 811 932 ED8 W-W

AVAILABLE IN

BLACK-BLACK 251 67 811 932 ED8 B-B

WHITE-WHITE 251 67 811 932 ED8 W-W



[View on website](#)



General info

LOCATION	indoor-outdoor
INSTALLATION	Ceiling Surface mounted
INGRESS PROTECTION	IP53
PROTECTION AGAINST MECHANICAL IMPACT	IK03
WEIGHT (KG)	0.5
ADJUSTABILITY	non adjustable
INFORMATION	REFLECTOR FL-33° INCL.DIMMABLE POWER SUPPLY 350mA-DC

Electrical info

ELECTRICAL	220-240V / 50-60Hz
CLASS	II
POWER SUPPLY	YES
DIM TYPE	mains (phase cut-off)
ENERGY CLASS	C
CERTIFICATES	CB, EAC, RCM

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 5,8W / CRI>90 (R9: 52) / 3000K / 787lm
TM-30 VALUES	Rf: 90 / Rg: 99
SDCM	SDCM1
RISKGROUP	RG1
LM80	L90B10 > 50000
LED TECHNICS (LIGHT SOURCE)	787lm // 5,8W // 135lm/W
LED TECHNICS (LUMINAIRE)	628lm // 7W // 94lm/W

For detailed installation instructions, please consult the manual: [251_67_811_XXX_ED8_HAND.pdf](#)

BOXY L+ 93033 DIM8 W-W

251 67 811 932 ED8 W-W

FINISH YOUR SPECIFICATION

Control gear, ballast and transformers



300 90 004 ED8 WIRELESS CONTROL DIM8

☐

Light altering devices



251 70 03 01 B BOXY HONEYCOMB B

☐



251 70 03 01 W BOXY HONEYCOMB W

☐



251 70 03 04 B BOXY SOFTENING LENS B

☐



251 70 03 04 W BOXY SOFTENING LENS W

☐



251 70 03 05 B BOXY GLASS SBL B

☐



251 70 03 05 W BOXY GLASS SBL W

☐

Notes: