



BOXY R 92733 DIM8 B-B

251 70 811 922 ED8 B-B

AVAILABLE IN

BLACK-BLACK 251 70 811 922 ED8 B-B



BLACK-FLEMISH BRONZE 251 70 811 922 ED8 B-FBR

BLACK-FLEMISH GOLD 251 70 811 922 ED8 B-FG

BLACK-GOLD MATT 251 70 811 922 ED8 B-MMAT

WHITE-BLACK 251 70 811 922 ED8 W-B

WHITE-WHITE 251 70 811 922 ED8 W-W



[View on website](#)

General info

LOCATION	indoor-outdoor
INSTALLATION	Ceiling Surface mounted
INGRESS PROTECTION	IP53
PROTECTION AGAINST MECHANICAL IMPACT	IK03
WEIGHT (KG)	0.6
ADJUSTABILITY	non adjustable
INFORMATION	REFLECTOR FL-33° INCL.DIMMABLE LED POWER SUPPLY 500mA-DC

Electrical info

ELECTRICAL	220-240V / 50-60Hz
CLASS	II
POWER SUPPLY	YES
DIM TYPE	mains (phase cut-off)
ENERGY CLASS	D
CERTIFICATES	CB, EAC, RCM

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 8,6W / CRI>90 (R9: 60) / 2700K / 1041lm
TM-30 VALUES	rf: 89 / Rg: 100
SDCM	SDCM1
RISKGROUP	RG1
LM80	L90B10 > 50000
LED TECHNICS (LIGHT SOURCE)	1041lm // 8,6W // 121lm/W
LED TECHNICS (LUMINAIRE)	815lm // 10W // 82lm/W

Accessories

BOXY HONEYCOMB
BOXY SOFTENING LENS
BOXY GLASS SBL

BOXY R 92733 DIM8 B-B

251 70 811 922 ED8 B-B

For detailed installation instructions, please consult the manual: [251_70_811_XXX_ED8_HAND.pdf](#)

FINISH YOUR SPECIFICATION

Miscellaneous control equipment




36,3 40,4 14


300 90 004 ED8 WIRELESS CONTROL DIM8

☐

Light altering devices



Ø40



Ø45 1,5

251 70 03 01 B BOXY HONEYCOMB B

☐

251 70 03 01 W BOXY HONEYCOMB W

☐



Ø40



Ø45 1,5

251 70 03 04 B BOXY SOFTENING LENS B

☐

251 70 03 04 W BOXY SOFTENING LENS W

☐



Ø40



Ø45 1,5

251 70 03 05 B BOXY GLASS SBL B

☐

251 70 03 05 W BOXY GLASS SBL W

☐



BOXY R 92733 DIM8 B-B

251 70 811 922 ED8 B-B

Notes: