





**BOXY R 92733 DIM8 B-FBR**  
251 70 811 922 ED8 B-FBR

AVAILABLE IN  
**BLACK-BLACK** 251 70 811 922 ED8 B-B  
**BLACK-FLEMISH BRONZE** 251 70 811 922 ED8 B-FBR  
**BLACK-FLEMISH GOLD** 251 70 811 922 ED8 B-FG  
**BLACK-GOLD MATT** 251 70 811 922 ED8 B-MMAT  
**WHITE-BLACK** 251 70 811 922 ED8 W-B  
**WHITE-WHITE** 251 70 811 922 ED8 W-W



 [View on website](#)



General info		
	LOCATION	indoor-outdoor
	INSTALLATION	Ceiling Surface mounted
	INGRESS PROTECTION	IP53
	PROTECTION AGAINST MECHANICAL IMPACT	IK03
	WEIGHT (KG)	0.6
	ADJUSTABILITY	non adjustable
	INFORMATION	REFLECTOR FL-33° INCL.DIMMABLE LED POWER SUPPLY 500mA-DC

Electrical info		
	ELECTRICAL	220-240V / 50-60Hz
	CLASS	II
	POWER SUPPLY	YES
	DIM TYPE	mains (phase cut-off)
	ENERGY CLASS	D
	CERTIFICATES	CB, EAC, RCM

Lightsource info		
	LIGHTSOURCE NAME	LED
	LIGHTSOURCE	LED array 8,6W / CRI>90 (R9: 60) / 2700K / 1041lm
	TM-30 VALUES	Rf: 89 / Rg: 100
	SDCM	SDCM1
	RISKGROUP	RG1
	LM80	L90B10 > 50000
	LED TECHNICS (LIGHT SOURCE)	1041lm // 8,6W // 121lm/W
	LED TECHNICS (LUMINAIRE)	815lm // 10W // 82lm/W

Accessories		
	BOXY HONEYCOMB	
	BOXY SOFTENING LENS	
	BOXY GLASS SBL	

**BOXY R 92733 DIM8 B-FBR**

251 70 811 922 ED8 B-FBR

For detailed installation instructions, please consult the manual: [251\\_70\\_811\\_XXX\\_ED8\\_HAND.pdf](#)

**FINISH YOUR SPECIFICATION**

**Control gear, ballast and transformers**



36,3 40,4 14

**300 90 004 ED8** WIRELESS CONTROL DIM8

☐

**Light altering devices**



Ø40

**251 70 03 01 B** BOXY HONEYCOMB B



Ø45 1,5

☐

**251 70 03 01 W** BOXY HONEYCOMB W

☐



Ø40

**251 70 03 04 B** BOXY SOFTENING LENS B




Ø45 1,5

☐

**251 70 03 04 W** BOXY SOFTENING LENS W

☐



Ø40

**251 70 03 05 B** BOXY GLASS SBL B



Ø45 1,5

☐

**251 70 03 05 W** BOXY GLASS SBL W

☐



## **BOXY R 92733 DIM8 B-FBR**

251 70 811 922 ED8 B-FBR

Notes: