

PARTOU AC 92733 DIM8

25217 9228 B



AVAILABLE IN

BLACK 25217 9228 B

FLEMISH BRONZE 25217 9228 FBR

FLEMISH GOLD 25217 9228 FG

WHITE 25217 9228 W



[View on website](#)



General info

| | |
|---|------------------|
| LOCATION | indoor |
| INSTALLATION | Ceiling Recessed |
| CUTOUT SHAPE/SIZE (MM) | round - 76 |
| RECESSED DEPTH (MM) | 90 |
| THICKNESS OF MOUNTING SURFACE (MM) | min.5 |
| INGRESS PROTECTION | IP20 |
| WEIGHT (KG) | 0.3 |
| ADJUSTABILITY | non adjustable |
| INFORMATION | REFLECTOR FL-33° |

Electrical info

| | |
|---------------------|-----------------------|
| ELECTRICAL | 230V / 50-60Hz |
| CLASS | I |
| DIM TYPE | mains (phase cut-off) |
| ENERGY CLASS | G |

Lightsource info

| | |
|------------------------------------|---|
| LIGHTSOURCE NAME | LED |
| LIGHTSOURCE | AC LED array 8W / CRI>90 (R9: 55) / 2700K / 597lm |
| TM-30 VALUES | rf: 92 / Rg: 98 |
| SDCM | SDCM3 |
| RISKGROUP | RG1 |
| LM80 | L80B10 > 67000 |
| BEAMANGLE | 33° |
| LED TECHNICS (LIGHT SOURCE) | 597lm // 8W // 75lm/W |
| LED TECHNICS (LUMINAIRE) | 504lm // 8W // 63lm/W |

Options

PLASTERKIT 101













For detailed installation instructions, please consult the manual : [25217_XXX8_HAND.pdf](#)

DELTALIGHT

PARTOU AC 92733 DIM8

25217 9228 B

CEILING COMPATIBILITY

| Ceiling Type | Mounting Kit |
|---|--|
|  System ceiling | - |
|  Plasterboard | - |
|  Stucanet |  202 11 19 - PLASTERKIT 101 Required |
|  Wood | - |
|  Concrete + plaster |  202 11 19 - PLASTERKIT 101 Required |
|  Lintel + plaster |  202 11 19 - PLASTERKIT 101 Required |
|  Hollow-core slab + plaster |  202 11 19 - PLASTERKIT 101 Required |
|  Stretched ceiling | - |

FINISH YOUR SPECIFICATION

Plasterkits



202 11 19 PLASTERKIT 101



Cutout dimension (mm): 80 x 180

Notes: