
DELTALIGHT




INFORM SQ P144-5 DOWN-UP 93067

REFERENCE 25514 9320 B-B

AVAILABLE IN
BLACK-BLACK 25514 9320 B-B
BLACK-FLEMISH GOLD 25514 9320 B-FG
WHITE-BLACK 25514 9320 W-B
WHITE-WHITE 25514 9320 W-W





View on website

General info	
LOCATION	indoor
INSTALLATION	Ceiling Suspended
INGRESS PROTECTION	IP20
WEIGHT (KG)	1.1
ADJUSTABILITY	non adjustable
INFORMATION	60 x REFLECTOR FL-67° (DOWN) EXCL.LED POWER SUPPLY 900mA-DC INCL.2 x CABLE SUSPENSION SINGLE AUTO. 1,6m POWER VIA CABLE SUSPENSION

Electrical info	
CLASS	III
DIM TYPE	depending on power supply
ENERGY CLASS	D
CERTIFICATES	CB, ENEC, EPD

Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	DOWN: LED cluster 17,6W / CRI>90 (R9: 50) / 3000K / 2670lm UP: LED cluster 14,1W / CRI>90 (R9: 50) / 3000K / 2136lm
TM-30 VALUES	Rf: 92 / Rg: 100
SDCM	SDCM3
RISKGROUP	RG1
LM80	L80 > 60000
BEAMANGLE	67°
LED TECHNICS (LIGHT SOURCE)	DOWN: 2670lm // 17,6W // 152lm/W UP: 2136lm // 14,1W // 152lm/W
LED TECHNICS (LUMINAIRE)	DOWN: 2264lm // 20W // 112lm/W UP: 1440lm // 16W // 89lm/W

Requirements

INFORM SQ POWERBOX 50W (DIM5)
INFORM POWER SUPPLY 45W + SUSPENSION+CONNECTION ST

For detailed installation instructions, please consult the manual : **25514_XXX0_HAND.pdf**

DELTALIGHT

INFORM SQ P144-5 DOWN-UP 93067

25514 9320 B-B


FINISH YOUR SPECIFICATION

Power box

# of Fixtures

Min current | Max current


ⓘ # of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.



25510 0010 B INFORM SQ POWERBOX 50W B — 1

Dimtype: non-dimmable

25510 0010 W INFORM SQ POWERBOX 50W W — 1



25510 0015 B INFORM SQ POWERBOX 50W DIM5 B — 1

Dimtype: DALI


25510 0015 W INFORM SQ POWERBOX 50W DIM5 W — 1

LED power supplies

# of Fixtures


Min current | Max current

ⓘ # of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.



25510 0385 INFORM POWER SUPPLY 45W DIM5 — 1

Dimtype: DALI



25510 0430 INFORM POWER SUPPLY 45W — 1

Dimtype: non-dimmable

Electric connection parts

# of Fixtures


Min current | Max current

ⓘ # of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.

DELTALIGHT

INFORM SQ P144-5 DOWN-UP 93067

25514 9320 B-B



15225 0350 B SUSPENSION + CONNECTION ST B — 2 needed ☐

Cutout dimension (mm): 27

15225 0350 W SUSPENSION + CONNECTION ST W — 2 needed ☐

Notes: