

## INFORM SQ P144-5 DOWN-UP 93067

25514 9320 B-B



AVAILABLE IN

**BLACK-BLACK** 25514 9320 B-B

**BLACK-FLEMISH GOLD** 25514 9320 B-FG

**WHITE-BLACK** 25514 9320 W-B

**WHITE-WHITE** 25514 9320 W-W



 [View on website](#)



### General info

<b>LOCATION</b>	indoor
<b>INSTALLATION</b>	Ceiling Suspended
<b>INGRESS PROTECTION</b>	IP20
<b>WEIGHT (KG)</b>	1.1
<b>ADJUSTABILITY</b>	non adjustable
<b>INFORMATION</b>	60 x REFLECTOR FL-67° (DOWN) EXCL.LED POWER SUPPLY 900mA-DC INCL.2 x CABLE SUSPENSION SINGLE AUTO. 1,6m POWER VIA CABLE SUSPENSION

### Electrical info

<b>CLASS</b>	III
<b>DIM TYPE</b>	depending on power supply
<b>ENERGY CLASS</b>	D
<b>CERTIFICATES</b>	CB, ENEC, EPD

### Lightsource info

<b>LIGHTSOURCE NAME</b>	LED
<b>LIGHTSOURCE</b>	DOWN: LED cluster 17,6W / CRI>90 (R9: 50) / 3000K / 2670lm UP: LED cluster 14,1W / CRI>90 (R9: 50) / 3000K / 2136lm
<b>TM-30 VALUES</b>	Rf: 92 / Rg: 100
<b>SDCM</b>	SDCM3
<b>RISKGROUP</b>	RG1
<b>LM80</b>	L80 > 60000
<b>BEAMANGLE</b>	67°
<b>LED TECHNICS (LIGHT SOURCE)</b>	DOWN: 2670lm // 17,6W // 152lm/W UP: 2136lm // 14,1W // 152lm/W
<b>LED TECHNICS (LUMINAIRE)</b>	DOWN: 2264lm // 20,2W // 112lm/W UP: 1440lm // 16,2W // 89lm/W

### Requirements

INFORM SQ POWERBOX 50W (DIM5)

INFORM POWER SUPPLY 45W + SUSPENSION+CONNECTION ST

For detailed installation instructions, please consult the manual : [25514\\_XXX0\\_HAND.pdf](#)

# DELTALIGHT

## INFORM SQ P144-5 DOWN-UP 93067

25514 9320 B-B

### FINISH YOUR SPECIFICATION

#### Power box

#### # of Fixtures



# of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.

Min current | Max current



**25510 0010 B** INFORM SQ POWERBOX 50W B

1

Dimtype: non-dimmable

**25510 0010 W** INFORM SQ POWERBOX 50W W

1



**25510 0015 B** INFORM SQ POWERBOX 50W DIM5 B

1

Dimtype: DALI

**25510 0015 W** INFORM SQ POWERBOX 50W DIM5 W

1

#### LED power supplies

#### # of Fixtures



# of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.

Min current | Max current



**25510 0385** INFORM POWER SUPPLY 45W DIM5

1

Dimtype: DALI



**25510 0430** INFORM POWER SUPPLY 45W

1

Dimtype: non-dimmable

#### Electric connection parts

#### # of Fixtures



# of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.

Min current | Max current

# DELTALIGHT

## INFORM SQ P144-5 DOWN-UP 93067

25514 9320 B-B



**15225 0350 B** SUSPENSION + CONNECTION ST B

2 needed

**Cutout dimension (mm): 27**

**15225 0350 W** SUSPENSION + CONNECTION ST W

2 needed

Notes: