DELTALIGHT



FRAX MB 93014

REFERENCE 26010 9310 N

AVAILABLE IN
FLEMISH BRONZE OUTDOOR 26010 9310 FBRX
ANTHRACITE 26010 9310 N
PINE GREEN 26010 9310 PGR





View on website

General info	
LOCATION	outdoor
INSTALLATION	Floor Surface mounted,Wall Surface mounted
INGRESS PROTECTION	IP65
PROTECTION AGAINST MECHANICAL IMPACT	IK08
WEIGHT (KG)	2.1
ADJUSTABILITY	0° to 120° swiveling, 360° rotatable
INFORMATION	9 x LENS SP-14° INCL.LED POWER SUPPLY 900mA-DC INCL.1 x CABLE H05 RN-F 3 x 1mm² 2m

Electrical info	
ELECTRICAL	220-240V / 50-60Hz
CLASS	I
POWER SUPPLY	YES
DIM TYPE	non-dimmable
ENERGY CLASS	E
CERTIFICATES	CB, ENEC, EPD, RCM

Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED cluster 23,4W / CRI>90 (R9: 60) / 3000K / 2654lm
TM-30 VALUES	Rf: 92 / Rg: 99
SDCM	SDCM3
RISKGROUP	RG2
LM80	L80 > 150000
BEAMANGLE	14°
LED TECHNICS (LIGHT SOURCE)	2654lm // 23,4W // 113lm/W
LED TECHNICS (LUMINAIRE)	2070lm // 27W // 77lm/W

Requirements

FRAX BRACKET
FRAX PIN
FRAX STRAP

Options

FRAX ANTI VANDAL SCREWS

Accessories

FRAX M KAP

DELTALIGHT

FRAX MB 93014

26010 9310 N

For detailed installation instructions, please consult the manual : **26010_XX10_HAND.pdf**

FINISH YOUR SPECIFICATION

Pins and plates for bollards



26070 0040 FBRX FRAX PIN FBRX ☐

26070 0040 N FRAX PIN N ☐

26070 0040 PGR FRAX PIN PGR ☐

Fixation components



26070 0060 FBRX FRAX BRACKET FBRX ☐

26070 0060 N FRAX BRACKET N ☐

26070 0060 PGR FRAX BRACKET PGR ☐

Light altering devices



26070 0020 N FRAX M KAP N ☐

DELTALIGHT

FRAX MB 93014

26010 9310 N

Other



26070 0030 FRAX ANTI VANDAL SCREWS 5 PCS ☐



26070 0050 N FRAX STRAP N ☐

Notes: