



DELTALIGHT



FRAX M 93047

26011 9380 N

AVAILABLE IN
ALU GREY 26011 9380 A
FLEMISH BRONZE OUTDOOR 26011 9380 FBRX
ANTHRACITE 26011 9380 N



 [View on website](#)



General info

LOCATION	outdoor
INSTALLATION	Floor Surface mounted, Wall Surface mounted
INGRESS PROTECTION	IP65
PROTECTION AGAINST MECHANICAL IMPACT	IK08
WEIGHT (KG)	2.4
ADJUSTABILITY	0° to 120° swiveling, 360° rotatable
INFORMATION	9 x LENS SP-14° INCLLED POWER SUPPLY 900mA-DC INCL.BEAM LENS 47°

Electrical info

ELECTRICAL	220-240V / 50-60Hz
CLASS	I
POWER SUPPLY	YES
DIM TYPE	non-dimmable
ENERGY CLASS	E
CERTIFICATES	CB, ENEC, EPD, RCM

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED cluster 23,4W / CRI>90 (R9: 60) / 3000K / 2654lm
TM-30 VALUES	Rf: 92 / Rg: 99
SDCM	SDCM3
RISKGROUP	RG2
LM80	L80 > 150000
BEAMANGLE	47°
LED TECHNICS (LIGHT SOURCE)	2654lm // 23,4W // 113lm/W
LED TECHNICS (LUMINAIRE)	1858lm // 26,9W // 69lm/W

Options

FRAX ANTI VANDAL SCREWS

Accessories

FRAX M KAP

For detailed installation instructions, please consult the manual : [26011_XX80_HAND.pdf](#)


DELTALIGHT

FRAX M 93047

26011 9380 N

FINISH YOUR SPECIFICATION

Light altering devices



26070 0020 N FRAX M KAP N

Other



26070 0030 FRAX ANTI VANDAL SCREWS 5 PCS

Notes: