DELTALIGHT

ODRON CLIP 92728/41

REFERENCE 26213 9200 B-B

AVAILABLE IN
BLACK-BLACK 26213 9200 B-B
WHITE-WHITE 26213 9200 W-W





View on website

General info	
LOCATION	indoor
INSTALLATION	Ceiling Semi-recessed
CUTOUT SHAPE/SIZE (MM)	round - 51
RECESSED DEPTH (MM)	40
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.2
ADJUSTABILITY	0° to 90° swiveling, 355° rotatable
INFORMATION	INCL.2 x INTERCHANGABLE REFLECTOR: FL-28° + WFL-41° EXCL.LED POWER SUPPLY 350-500mA-DC

Electrical info	
CLASS	III
DIM TYPE	depending on power supply
ENERGY CLASS	E
CERTIFICATES	CB, ENEC

Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 5,8-8,6W / CRI>90 (R9: 60) / 2700K / 702-974lm
TM-30 VALUES	Rf: 89 / Rg: 100
SDCM	SDCM1
RISKGROUP	RG1
LM80	L90B10 > 50000
BEAMANGLE	28°/41°
LED TECHNICS (LIGHT SOURCE)	974lm // 8,6W // 113lm/W
LED TECHNICS (LUMINAIRE)	816lm // 9,9W // 83lm/W

Requirements

LED POWER SUPPLY 350 / 500mA-DC DIM

Options

MOUNTING KIT FLUSH SPY

Accessories

ODRON COVER

DELTALIGHT

ODRON CLIP 92728/41

26213 9200 B-B

For detailed installation instructions, please consult the manual : **26213_XXX0_HAND.pdf**

CEILING COMPATIBILITY

Ceiling Type	Mounting Kit	
System ceiling	414 90 01 - MOUNTING KIT FLUSH SPY	Required
Plasterboard	414 90 01 - MOUNTING KIT FLUSH SPY	Required
Stucanet	414 90 01 - MOUNTING KIT FLUSH SPY	Required
Wood	-	
Concrete	-	
Concrete + plaster	414 90 01 - MOUNTING KIT FLUSH SPY	Required
Lintel + plaster	414 90 01 - MOUNTING KIT FLUSH SPY	Required
Hollow-core slab	-	
Hollow-core slab + plaster	414 90 01 - MOUNTING KIT FLUSH SPY	Required
Stretched ceiling	-	

FINISH YOUR SPECIFICATION

LED power supplies

of Fixtures

Min current | Max current

ⓘ # of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.



300 48 350 ED1 LED POWER CONVERTER 48V-DC to 350 mA-DC / 15W DIM1 — 2

Dimtype: 1-10V

Cutout dimension (mm): 30

ODRON CLIP 92728/41

26213 9200 B-B



300 48 350 ED5 LED POWER CONVERTER 48V-DC to 350 mA-DC / 15W DIM5 — 2

Dimtype: DALI

Cutout dimension (mm): 45



300 48 350 MDL LED POWER CONVERTER 48V-DC to 350 mA-DC / 15W MDL — 2

Dimtype: non-dimmable

Cutout dimension (mm): 30



300 48 350 WDL LED POWER CONVERTER 48V-DC to 350 mA-DC / 15W WDL — 2

Dimtype: WDL = wireless dimmable

Cutout dimension (mm): 45



300 48 500 ED1 LED POWER CONVERTER 48V-DC to 500 mA-DC / 22W DIM1 — 2

Dimtype: 1-10V

Cutout dimension (mm): 30



300 48 500 ED5 LED POWER CONVERTER 48V-DC to 500 mA-DC / 22W DIM5 — 2

Dimtype: DALI

Cutout dimension (mm): 45



300 48 500 MDL LED POWER CONVERTER 48V-DC to 500 mA-DC / 22W MDL — 2

Dimtype: non-dimmable

Cutout dimension (mm): 30



300 48 500 WDL LED POWER CONVERTER 48V-DC to 500 mA-DC / 22W WDL — 2

Dimtype: WDL = wireless dimmable

Cutout dimension (mm): 45



300 90 61 LED POWER SUPPLY MULTI-POWER DIM6 — 2 | 2

Dimtype: mains (phase cut-off) or push button

Cutout dimension (mm): 56



300 90 63 LED POWER SUPPLY MULTI-POWER DIM9 — 4(4) | 4(4)

Dimtype: 1-10V or DALI or push button

Cutout dimension (mm): 82



300 90 64 LED POWER SUPPLY MULTI-POWER DIM7 — 3(2) | 2(1)

Dimtype: 1-10V or push button

Cutout dimension (mm): 72

DELTALIGHT

ODRON CLIP 92728/41

26213 9200 B-B



300 90 67 LED POWER CONVERTER 24V-DC TO MULTI CURRENT 48W DIM9 2 | -

Dimtype: 1-10V or DALI or push button



300 90 68 LED POWER SUPPLY MULTI-POWER DIM5 2(2) | 2(1)

Dimtype: DALI

Cutout dimension (mm): 72



300 90 69 LED POWER SUPPLY MULTI-POWER HV DIM9 2->6(6) | 6(4)

Dimtype: 1-10V or DALI or push button

Cutout dimension (mm): 84



300 90 124 LED POWER SUPPLY MULTI-POWER DIM7 2(2) | 2(1)

Dimtype: 1-10V or push button

Cutout dimension (mm): 55



300 90 125 LED POWER SUPPLY MULTI-POWER MINI DIM5 2(2) | 2(1)

Dimtype: DALI

Cutout dimension (mm): 55



300 90 135 LED POWER SUPPLY MULTI-POWER HV 3->4 | 2->4

Dimtype: non-dimmable

Cutout dimension (mm): 90



21012 0010 LED POWER SUPPLY MULTI POWER 2 | 2

Dimtype: non-dimmable

Cutout dimension (mm): 50



21012 0021 LED POWER SUPPLY MULTI POWER DIM1 3 | 3

Dimtype: 1-10V

Cutout dimension (mm): 54



21012 0035 LED POWER SUPPLY MULTI POWER DIM5 3 | 3

Dimtype: DALI

Cutout dimension (mm): 54



21012 004W LED POWER SUPPLY MULTI-POWER WDL 4(4) | 4(3)

Dimtype: WDL = wireless dimmable

Cutout dimension (mm): 84

DELTALIGHT

ODRON CLIP 92728/41

26213 9200 B-B



21012 005W LED POWER SUPPLY MULTI-POWER COMPACT WDL 3 | 3

Dimtype: WDL = wireless dimmable

Cutout dimension (mm): 54



21012 0258 LED POWER SUPPLY MULTI POWER 200-350 / 10W DIM8 1

Dimtype: mains (phase cut-off)

Cutout dimension (mm): 50



21012 0268 LED POWER SUPPLY MULTI POWER 200-350 / 15W DIM8 2->2

Dimtype: mains (phase cut-off)

Cutout dimension (mm): 50



21012 0278 LED POWER SUPPLY MULTI POWER 500-700 / 20W DIM8 1

Dimtype: mains (phase cut-off)

Cutout dimension (mm): 55



21012 0288 LED POWER SUPPLY MULTI POWER 500-700 / 36W DIM8 2->3

Dimtype: mains (phase cut-off)

Cutout dimension (mm): 55



21012 0298 LED POWER SUPPLY MULTI POWER 250-900 / 20W DIM8 2 | 2

Dimtype: mains (phase cut-off)

Cutout dimension (mm): 48



21012 0308 LED POWER SUPPLY 350mA / 7,35W DIM8 1

Dimtype: mains (phase cut-off)

Cutout dimension (mm): 40



21012 0318 LED POWER SUPPLY 500mA / 10W DIM8 1

Dimtype: mains (phase cut-off)

Cutout dimension (mm): 40



21012 0480 LED POWER SUPPLY 350mA-DC / 17W IP68 2(2)

Dimtype: non-dimmable

Cutout dimension (mm): 60



21012 0500 LED POWER SUPPLY 500mA-DC / 24W IP68 2(1)

Dimtype: non-dimmable

Cutout dimension (mm): 60

DELTALIGHT

ODRON CLIP 92728/41

26213 9200 B-B



21032 0295 LED POWER CONVERTER 48V-DC to 350 mA-DC / 15W DIM5 2

Dimtype: DALI

Cutout dimension (mm): 30



21032 0305 LED POWER CONVERTER 48V-DC to 500 mA-DC / 22W DIM5 2

Dimtype: DALI

Cutout dimension (mm): 30

Mounting kits



414 90 01 MOUNTING KIT FLUSH SPY

Cutout dimension (mm): 83

Decorative ornaments

26210 0020 GC ODRON COVER GC

Notes: