



## NIME II TRIMLESS 92735

26413 9220



 [View on website](#)



### General info

<b>LOCATION</b>	indoor
<b>INSTALLATION</b>	Ceiling Recessed
<b>CUTOUT SHAPE/SIZE (MM)</b>	round - 54
<b>RECESSED DEPTH (MM)</b>	90
<b>THICKNESS OF MOUNTING SURFACE (MM)</b>	9,5-12,5
<b>INGRESS PROTECTION</b>	IP20
<b>WEIGHT (KG)</b>	0.3
<b>ADJUSTABILITY</b>	non adjustable
<b>INFORMATION</b>	LENS FL-35° EXCL.LED POWER SUPPLY 350-700mA-DC

### Electrical info

<b>CLASS</b>	III
<b>DIM TYPE</b>	depending on power supply
<b>ENERGY CLASS</b>	G
<b>CERTIFICATES</b>	CB, ENEC

### Lightsource info

<b>LIGHTSOURCE NAME</b>	LED
<b>LIGHTSOURCE</b>	LED array 3,9-8,2W / CRI>90 (R9: 56) / 2700K / 385-677lm
<b>TM-30 VALUES</b>	rf: 91 / Rg: 99
<b>SDCM</b>	SDCM2
<b>RISKGROUP</b>	RG2 (threshold 0,6m)
<b>LM80</b>	L90B10 > 41000
<b>BEAMANGLE</b>	35°
<b>LED TECHNICS (LIGHT SOURCE)</b>	677lm // 8,2W // 83lm/W
<b>LED TECHNICS (LUMINAIRE)</b>	420lm // 9,4W // 45lm/W

### Remarks

Access above ceiling required

### Requirements

LED POWER SUPPLY 350 / 500 / 700mA-DC DIM (Remote)



For detailed installation instructions, please consult the manual : [26413\\_XXX0\\_HAND.pdf](#)

# DELTALIGHT








## NIME II TRIMLESS 92735

26413 9220

### CEILING COMPATIBILITY

Ceiling Type	Mounting Kit
 System ceiling	-
 Plasterboard	-

### FINISH YOUR SPECIFICATION

LED power supplies	# of Fixtures
	Min current   Max current
<p> # of fixtures indicates how many devices can be connected (min -&gt; max) to the power supply. The values before and after the ' ' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.</p>	
 <p><b>300 48 350 ED1</b> LED POWER CONVERTER 48V-DC to 350 mA-DC / 15W DIM1            Dimtype: 1-10V            Cutout dimension (mm): 30</p>	3 <input type="checkbox"/>
 <p><b>300 48 350 ED5</b> LED POWER CONVERTER 48V-DC to 350 mA-DC / 15W DIM5            Dimtype: DALI            Cutout dimension (mm): 45</p>	3 <input type="checkbox"/>
 <p><b>300 48 350 MDL</b> LED POWER CONVERTER 48V-DC to 350 mA-DC / 15W MDL            Dimtype: non-dimmable            Cutout dimension (mm): 30</p>	3 <input type="checkbox"/>
 <p><b>300 48 350 WDL</b> LED POWER CONVERTER 48V-DC to 350 mA-DC / 15W WDL            Dimtype: WDL = wireless dimmable            Cutout dimension (mm): 45</p>	3 <input type="checkbox"/>
 <p><b>300 48 500 ED1</b> LED POWER CONVERTER 48V-DC to 500 mA-DC / 22W DIM1            Dimtype: 1-10V            Cutout dimension (mm): 30</p>	3 <input type="checkbox"/>
 <p><b>300 48 500 ED5</b> LED POWER CONVERTER 48V-DC to 500 mA-DC / 22W DIM5            Dimtype: DALI            Cutout dimension (mm): 45</p>	3 <input type="checkbox"/>

# DELTALIGHT

## NIME II TRIMLESS 92735

26413 9220



**300 48 500 MDL** LED POWER CONVERTER 48V-DC to 500 mA-DC / 22W MDL

3



Dimtype: non-dimmable

Cutout dimension (mm): 30




**300 48 500 WDL** LED POWER CONVERTER 48V-DC to 500 mA-DC / 22W WDL

3



Dimtype: WDL = wireless dimmable

Cutout dimension (mm): 45




**300 48 700 ED1** LED POWER CONVERTER 48V-DC to 700 mA-DC / 25W DIM1

3



Dimtype: 1-10V

Cutout dimension (mm): 30




**300 48 700 ED5** LED POWER CONVERTER 48V-DC to 700 mA-DC / 25W DIM5

3



Dimtype: DALI

Cutout dimension (mm): 45




**300 48 700 MDL** LED POWER CONVERTER 48V-DC to 700 mA-DC / 25W MDL

3



Dimtype: non-dimmable

Cutout dimension (mm): 30




**300 48 700 WDL** LED POWER CONVERTER 48V-DC to 700 mA-DC / 25W WDL

3



Dimtype: WDL = wireless dimmable

Cutout dimension (mm): 45




**300 90 61** LED POWER SUPPLY MULTI-POWER DIM6

3 | 3 | 3



Dimtype: mains (phase cut-off) or push button

Cutout dimension (mm): 56




**300 90 63** LED POWER SUPPLY MULTI-POWER DIM9

6(6) | 6(6) | 6(4)



Dimtype: 1-10V or DALI or push button

Cutout dimension (mm): 82




**300 90 64** LED POWER SUPPLY MULTI-POWER DIM7

2->4(3) | 4(2) | 3(1)



Dimtype: 1-10V or push button

Cutout dimension (mm): 72



**300 90 67** LED POWER CONVERTER 24V-DC TO MULTI CURRENT 48W DIM9

3 | 3



Dimtype: 1-10V or DALI or push button

# DELTALIGHT

## NIME II TRIMLESS 92735

26413 9220




**300 90 68** LED POWER SUPPLY MULTI-POWER DIM5

4(3) | 4(2) | 3(1)



Dimtype: DALI

Cutout dimension (mm): 72



**300 90 69** LED POWER SUPPLY MULTI-POWER HV DIM9

2->9(10) | 9(6) | 7(4)



Dimtype: 1-10V or DALI or push button

Cutout dimension (mm): 84



**300 90 124** LED POWER SUPPLY MULTI-POWER DIM7

2->4(3) | 3(2) | 2(1)



Dimtype: 1-10V or push button

Cutout dimension (mm): 55




**300 90 125** LED POWER SUPPLY MULTI-POWER MINI DIM5

4(3) | 3(2) | 2(1)



Dimtype: DALI

Cutout dimension (mm): 55




**300 90 135** LED POWER SUPPLY MULTI-POWER HV

5->7 | 4->7 | 4->6 | 3->6



Dimtype: non-dimmable

Cutout dimension (mm): 90




**21012 0010** LED POWER SUPPLY MULTI POWER

2->3 | 3 | 3



Dimtype: non-dimmable

Cutout dimension (mm): 50




**21012 0021** LED POWER SUPPLY MULTI POWER DIM1

4 | 4 | 4



Dimtype: 1-10V

Cutout dimension (mm): 54




**21012 0035** LED POWER SUPPLY MULTI POWER DIM5

4 | 4 | 4



Dimtype: DALI

Cutout dimension (mm): 54




**21012 004W** LED POWER SUPPLY MULTI-POWER WDL

6(6) | 5(5) | 5(4)



Dimtype: WDL = wireless dimmable

Cutout dimension (mm): 84



**21012 005W** LED POWER SUPPLY MULTI-POWER COMPACT WDL

4 | 4 | 4



Dimtype: WDL = wireless dimmable

Cutout dimension (mm): 54

# DELTALIGHT

## NIME II TRIMLESS 92735

26413 9220



**21012 0258** LED POWER SUPPLY MULTI POWER 200-350 / 10W DIM8

2->2

**Dimtype: mains (phase cut-off)**

**Cutout dimension (mm): 50**



**21012 0268** LED POWER SUPPLY MULTI POWER 200-350 / 15W DIM8

3->3

**Dimtype: mains (phase cut-off)**

**Cutout dimension (mm): 50**



**21012 0278** LED POWER SUPPLY MULTI POWER 500-700 / 20W DIM8

2->2 | 2->2

**Dimtype: mains (phase cut-off)**

**Cutout dimension (mm): 55**



**21012 0288** LED POWER SUPPLY MULTI POWER 500-700 / 36W DIM8

3->4 | 3->4

**Dimtype: mains (phase cut-off)**

**Cutout dimension (mm): 55**




**21012 0298** LED POWER SUPPLY MULTI POWER 250-900 / 20W DIM8

3 | 3 | 2

**Dimtype: mains (phase cut-off)**

**Cutout dimension (mm): 48**




**21012 0480** LED POWER SUPPLY 350mA-DC / 17W IP68

4(3)

**Dimtype: non-dimmable**

**Cutout dimension (mm): 60**




**21012 0490** LED POWER SUPPLY 700mA-DC / 30W IP68

3(1)

**Dimtype: non-dimmable**

**Cutout dimension (mm): 60**




**21012 0500** LED POWER SUPPLY 500mA-DC / 24W IP68

4(2)

**Dimtype: non-dimmable**

**Cutout dimension (mm): 60**




**21032 0295** LED POWER CONVERTER 48V-DC to 350 mA-DC / 15W DIM5

3

**Dimtype: DALI**

**Cutout dimension (mm): 30**



**21032 0305** LED POWER CONVERTER 48V-DC to 500 mA-DC / 22W DIM5

3


**Dimtype: DALI**

**Cutout dimension (mm): 30**

# DELTALIGHT

## NIME II TRIMLESS 92735

26413 9220



**21032 0315**

LED POWER CONVERTER 48V-DC to 700 mA-DC / 25W DIM5

3



**Dimtype: DALI**

**Cutout dimension (mm): 30**

Notes: