




SL19 - PROFILE 2m B

27011 0050 B

AVAILABLE IN
BLACK 27011 0050 B
WHITE 27011 0050 W



 [View on website](#)

General info	
LOCATION	indoor
INSTALLATION	Ceiling Surface mounted
WEIGHT (KG)	1.4
INFORMATION	L : 2m 2 x 48V CONDUCTORS 2 DIM CONDUCTORS (For individual DALI dimming)
Electrical info	
CLASS	III
CERTIFICATES	UL


For detailed installation instructions, please consult the manual: [27011_0050_HAND.pdf](#)

SL19 - PROFILE 2m B


27011 0050 B

COMPATIBLE PARTS

Corners




27011 0630 SL19 - CORNER 90°




27011 0670 SL19 - CORNER V90°




Current supply




27011 0910 SL19 - SUPPLY 48V



27011 9910 SPL14 - CONNECTOR 48V - 180°




27011 9920 SL19 - CONNECTOR 48V - 90°



27011 9930 SL19 - CONNECTOR 48V - V90°

End caps




27011 0310 SL19 - END CAP SET




SL19 - PROFILE 2m B

27011 0050 B


LED power supplies




300 89 48 100 LED POWER SUPPLY 48V-DC / 100W DIN



300 89 48 240 LED POWER SUPPLY 48V-DC / 240W DIN




21012 0230 LED POWER SUPPLY 48V-DC / 100W



21012 0240 LED POWER SUPPLY 48V-DC / 200W


Profile




27011 0050 SL19 - PROFILE 2m



SMART 48



300 90 011 SMART 48 MODULATOR DIM9




300 90 012 SMART 48 MODULATOR WD

SL19 - PROFILE 2m B


27011 0050 B

COMPATIBLE LUMINAIRES

SHIFTLINE 19 - SPY 27




27031 9225 SL19 - SPY 27 L 92730 DIM5




27031 9325 SL19 - SPY 27 L 93030 DIM5


SHIFTLINE 19 - SPY 39




27033 9225 SL19 - SPY 39 L 92720 DIM5



27033 9235 SL19 - SPY 39 L 92740 DIM5




27033 9325 SL19 - SPY 39 L 93020 DIM5




27033 9335 SL19 - SPY 39 L 93040 DIM5

SHIFTLINE 19 - UHO



27029 9225 SL19 - UHO L 92730 DIM5



27029 9325 SL19 - UHO L 93030 DIM5

SL19 - PROFILE 2m B

27011 0050 B

Notes: