





SL19 - SPY 27 92730 MDL B

27022 9220 B

AVAILABLE IN
BLACK 27022 9220 B
FLEMISH BRONZE 27022 9220 FBR
FLEMISH GOLD 27022 9220 FG
GOLD COLOURED 27022 9220 GC
WHITE 27022 9220 W



[View on website](#)

General info

LOCATION	indoor
INSTALLATION	Low voltage systems Low voltage system mounted
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.2
ADJUSTABILITY	0° to 85° swiveling, 355° rotatable
INFORMATION	REFLECTOR FL-30° EXCL LED POWER SUPPLY 48V-DC SPY 27 TUBE B included

Electrical info

ELECTRICAL	48V-DC
CLASS	III
DIM TYPE	MDL = 1-10V or DALI or push button
ENERGY CLASS	D

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 5,8W / CRI>90 (R9: 60) / 2700K / 753lm
TM-30 VALUES	Rf: 89 / Rg: 100
SDCM	SDCM1
RISKGROUP	RG1
LM80	L90B10 > 50000
LED TECHNICS (LIGHT SOURCE)	753lm // 5,8W // 129lm/W
LED TECHNICS (LUMINAIRE)	459lm // 7W // 69lm/W

Requirements

LED POWER SUPPLY 48V-DC

Options

DIMMABLE MODULATOR

Accessories

Delta Light NV may revise the information and technical data at any time without notice. Version: 13/03/2024



SL19 - SPY 27 92730 MDL B

27022 9220 B

For detailed installation instructions, please consult the manual: [27022_XXX0_HAND.pdf](#)


SL19 - SPY 27 92730 MDL B

27022 9220 B

FINISH YOUR SPECIFICATION


SMART 48

#



300 90 011 SMART 48 MODULATOR DIM9

28

☐



300 90 012 SMART 48 MODULATOR WD

28

☐


LED power supplies

#




300 89 48 100 LED POWER SUPPLY 48V-DC / 100W DIN

15

☐



300 89 48 240 LED POWER SUPPLY 48V-DC / 240W DIN

36

☐


21012 0230 LED POWER SUPPLY 48V-DC / 100W

15

☐


21012 0240 LED POWER SUPPLY 48V-DC / 200W

30

☐

Light altering devices




24144 0040 B VISOR 27 B

☐


SL19 - SPY 27 92730 MDL B
27022 9220 B

COMPATIBLE COMPOSABLES

SHIFTLINE 19 profile	Available Colours
----------------------	-------------------



27011 0050 SL19 - PROFILE 2m



27011 0060 SL19 - PROFILE 3m



Notes: