



## SL19 - SPY 27 92730 MDL

27022 9220 B

AVAILABLE IN



**BLACK** 27022 9220 B

**FLEMISH BRONZE** 27022 9220 FBR

**FLEMISH GOLD** 27022 9220 FG

**GOLD COLOURED** 27022 9220 GC

**WHITE** 27022 9220 W



[View on website](#)



### General info

<b>LOCATION</b>	indoor
<b>INSTALLATION</b>	Low voltage systems Low voltage system mounted
<b>INGRESS PROTECTION</b>	IP20
<b>WEIGHT (KG)</b>	0.2
<b>ADJUSTABILITY</b>	0° to 85° swiveling, 355° rotatable
<b>INFORMATION</b>	REFLECTOR FL-30° EXCLLED POWER SUPPLY 48V-DC SPY 27 TUBE included (B for all versions W for FW version)

### Electrical info

<b>ELECTRICAL</b>	48V-DC
<b>CLASS</b>	III
<b>DIM TYPE</b>	MDL = 1-10V or DALI or push button
<b>ENERGY CLASS</b>	D
<b>CERTIFICATES</b>	CB, ENEC

### Lightsource info

<b>LIGHTSOURCE NAME</b>	LED
<b>LIGHTSOURCE</b>	LED array 5,8W / CRI>90 (R9: 60) / 2700K / 753lm
<b>TM-30 VALUES</b>	rf: 89 / Rg: 100
<b>SDCM</b>	SDCM1
<b>RISKGROUP</b>	RG1
<b>LM80</b>	L90B10 > 50000
<b>BEAMANGLE</b>	30°
<b>LED TECHNICS (LIGHT SOURCE)</b>	753lm // 5,8W // 129lm/W
<b>LED TECHNICS (LUMINAIRE)</b>	459lm // 6,7W // 69lm/W

### Requirements

LED POWER SUPPLY 48V-DC

### Options

DIMMABLE MODULATOR

### Accessories

VISOR 27

# DELTALIGHT

## SL19 - SPY 27 92730 MDL


27022 9220 B

For detailed installation instructions, please consult the manual : [27022\\_XXX0\\_HAND.pdf](#)


### FINISH YOUR SPECIFICATION

#### SMART 48

#### # of Fixtures

 # of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.

Min current | Max current



**300 90 011** SMART 48 MODULATOR DIM9

28

Dimtype: 1-10V or DALI or push button




**300 90 012** SMART 48 MODULATOR WD

28

Dimtype: WDL = wireless dimmable

#### LED power supplies

#### # of Fixtures

 # of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.

Min current | Max current



**300 89 48 100** LED POWER SUPPLY 48V-DC / 100W DIN

15


Dimtype: non-dimmable



**300 89 48 240** LED POWER SUPPLY 48V-DC / 240W DIN

36

Dimtype: non-dimmable



**21012 0230** LED POWER SUPPLY 48V-DC / 100W

15


Dimtype: non-dimmable

Cutout dimension (mm): 40

# DELTALIGHT

## SL19 - SPY 27 92730 MDL

27022 9220 B



**21012 0240** LED POWER SUPPLY 48V-DC / 200W

30



Dimtype: non-dimmable

Cutout dimension (mm): 40

### Light altering devices




**24144 0040 B** VISOR 27 B




## COMPATIBLE COMPOSABLES

### SHIFTLINE 19 profile

### Available Colours



**27011 0050** SL19 - PROFILE 2m



**27011 0060** SL19 - PROFILE 3m



Notes: