





SUPERNOVA XS 260 X 930 N

274 87 2610 93 N

AVAILABLE IN

ANTHRACITE (DARK GREY) 274 87 2610 93 N

WHITE 274 87 2610 93 W



[View on website](#)

General info

| | |
|---|---|
| LOCATION | outdoor |
| INSTALLATION | Ceiling Surface mounted, Wall Surface mounted |
| INGRESS PROTECTION | IP64 |
| PROTECTION AGAINST MECHANICAL IMPACT | IK03 |
| WEIGHT (KG) | 2.2 |
| ADJUSTABILITY | non adjustable |
| INFORMATION | INCL.GLASS OPAL |

Electrical info

| | |
|---------------------|--------------------|
| ELECTRICAL | 220-240V / 50-60Hz |
| CLASS | I |
| DIM TYPE | non-dimmable |
| ENERGY CLASS | D |

Lightsource info

| | |
|------------------------------------|--|
| LIGHTSOURCE NAME | LED |
| LIGHTSOURCE | LED cluster 9,6W / CRI>90 (R9: 50) / 3000K / 165lm |
| TM-30 VALUES | Rf: 92 / Rg: 100 |
| SDCM | SDCM3 |
| RISKGROUP | RG2 |
| LM80 | L80 > 60000 |
| LED TECHNICS (LIGHT SOURCE) | 165lm // 9,6W // 172lm/W |
| LED TECHNICS (LUMINAIRE) | 972lm // 11W // 88lm/W |

For detailed installation instructions, please consult the manual: [274_87_2610_XX_HAND.pdf](#)



SUPERNOVA XS 260 X 930 N

274 87 2610 93 N

Notes: