





SUPERNOVA XS PIVOT 260 X 930 W

274 88 2610 93 W

AVAILABLE IN

ANTHRACITE (DARK GREY) 274 88 2610 93 N

WHITE 274 88 2610 93 W



[View on website](#)



General info

LOCATION	outdoor
INSTALLATION	Ceiling Surface mounted, Wall Surface mounted
INGRESS PROTECTION	IP64
PROTECTION AGAINST MECHANICAL IMPACT	IK03
WEIGHT (KG)	2.9
ADJUSTABILITY	non adjustable
INFORMATION	INCL.GLASS OPAL

Electrical info

ELECTRICAL	220-240V / 50-60Hz
CLASS	I
DIM TYPE	non-dimmable
ENERGY CLASS	D

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED cluster 9,6W / CRI>90 (R9: 50) / 3000K / 1651lm
TM-30 VALUES	Rf: 92 / Rg: 100
SDCM	SDCM3
RISKGROUP	RG2
LM80	L80 > 60000
LED TECHNICS (LIGHT SOURCE)	1651lm // 9,6W // 172lm/W
LED TECHNICS (LUMINAIRE)	972lm // 11W // 88lm/W

For detailed installation instructions, please consult the manual: [274_88_2610_83_HAND.pdf](#)



SUPERNOVA XS PIVOT 260 X 930 W

274 88 2610 93 W

Notes: