





WA-T SOFT DIM8

275 15 1902 ED8 W-W

AVAILABLE IN

BLACK-GOLD MATT 275 15 1902 ED8 B-MMAT

WHITE-WHITE 275 15 1902 ED8 W-W



[View on website](#)



General info

LOCATION	indoor
INSTALLATION	Wall Surface mounted
INGRESS PROTECTION	IP20
WEIGHT (KG)	1.3
ADJUSTABILITY	non adjustable
INFORMATION	INCL.DIMMABLE LED POWER SUPPLY 250mA-DC

Electrical info

ELECTRICAL	220-240V / 50-60Hz
CLASS	I
POWER SUPPLY	YES
DIM TYPE	mains (phase cut-off)
ENERGY CLASS	G
CERTIFICATES	CB, ENEC, RCM

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 9W / CRI>90 / 3000-2000K / 690lm
LED TECHNICS (LIGHT SOURCE)	690lm // 9W // 77lm/W
LED TECHNICS (LUMINAIRE)	446lm // 10,4W // 43lm/W


For detailed installation instructions, please consult the manual : [275_15_1902_ED8_HAND.pdf](#)

WA-T SOFT DIM8

275 15 1902 ED8 W-W

FINISH YOUR SPECIFICATION

Miscellaneous control equipment



300 90 004 ED8 WIRELESS CONTROL DIM8

Dimtype: WDL = wireless dimmable

Cutout dimension (mm): 40



Notes: