DELTALIGHT



OUTLINER 100 930

REFERENCE 27810 9300 N

AVAILABLE IN
ANTHRACITE 27810 9300 N





View on website

General info	
LOCATION	outdoor
INSTALLATION	Floor Surface mounted
INGRESS PROTECTION	IP54
PROTECTION AGAINST MECHANICAL IMPACT	IK03
WEIGHT (KG)	2.4
ADJUSTABILITY	non adjustable
INFORMATION	EXCL.LED POWER SUPPLY 24V-DC

Electrical info	
ELECTRICAL	24V-DC
CLASS	III
DIM TYPE	depending on power supply
ENERGY CLASS	F

Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED LED FLEX OUT 4,75W / CRI>90 / 3000K / 494lm
LED TECHNICS (LIGHT SOURCE)	494lm // 4,75W // 104lm/W
LED TECHNICS (LUMINAIRE)	148lm // 5W // 27lm/W

Requirements

LED POWER SUPPLY 24V-DC (PWM)

Options

CBOX
PIN 11

For detailed installation instructions, please consult the manual : **27810_XXX0_HAND.pdf**

DELTALIGHT

OUTLINER 100 930

27810 9300 N

FINISH YOUR SPECIFICATION

LED power supplies

of Fixtures

Min current | Max current

ⓘ # of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.



300 89 24 150 LED POWER SUPPLY 24V-DC / 150W — 29

Dimtype: non-dimmable

Cutout dimension (mm): 75



300 90 61 LED POWER SUPPLY MULTI-POWER DIM6 — 3

Dimtype: mains (phase cut-off) or push button

Cutout dimension (mm): 56



21012 0101 LED POWER SUPPLY 24V-DC / 60W IP67 DIM1 — 11

Dimtype: 1-10V

Cutout dimension (mm): 65



21012 0111 LED POWER SUPPLY 24V-DC / 90W IP67 DIM1 — 17

Dimtype: 1-10V

Cutout dimension (mm): 75



21012 0121 LED POWER SUPPLY 24V-DC / 120W IP67 DIM1 — 23

Dimtype: 1-10V

Cutout dimension (mm): 75



21012 0135 LED POWER SUPPLY 24V-DC / 60W IP67 DIM5 — 11

Dimtype: DALI

Cutout dimension (mm): 65



21012 0145 LED POWER SUPPLY 24V-DC / 90W IP67 DIM5 — 17

Dimtype: DALI

Cutout dimension (mm): 75



21012 0155 LED POWER SUPPLY 24V-DC / 120W IP67 DIM5 — 23

Dimtype: DALI

Cutout dimension (mm): 75

OUTLINER 100 930

27810 9300 N



21012 0160 LED POWER SUPPLY 24V-DC / 24W 4

Dimtype: non-dimmable

Cutout dimension (mm): 55



21012 0171 LED POWER SUPPLY 24V-DC / 60W DIM1 11

Dimtype: 1-10V

Cutout dimension (mm): 61



21012 0181 LED POWER SUPPLY 24V-DC / 90W DIM1 17

Dimtype: 1-10V

Cutout dimension (mm): 70



21012 0191 LED POWER SUPPLY 24V-DC / 120W DIM1 23

Dimtype: 1-10V

Cutout dimension (mm): 70



21012 0205 LED POWER SUPPLY 24V-DC / 60W DIM5 11

Dimtype: DALI

Cutout dimension (mm): 61



21012 0225 LED POWER SUPPLY 24V-DC / 100W DIM5 19

Dimtype: DALI

Cutout dimension (mm): 70

Waterproof connection parts



216 12 00 CBOX

Cutout dimension (mm): 142 x 142

Pins and plates for bollards



229 01 11 PIN 11

OUTLINER 100 930

27810 9300 N

Notes: