





ULTRA X LED 930 A

279 61 811 930 A

AVAILABLE IN  
**ALU GREY** 279 61 811 930 A  
**ANTHRACITE (DARK GREY)** 279 61 811 930 N  
**WHITE** 279 61 811 930 W



 [View on website](#)



General info	
LOCATION	indoor-outdoor
INSTALLATION	Wall Surface mounted
INGRESS PROTECTION	IP55
PROTECTION AGAINST MECHANICAL IMPACT	IK03
WEIGHT (KG)	0.6
ADJUSTABILITY	non adjustable
INFORMATION	INCL.LENS INCL.LED POWER SUPPLY 350mA-DC

Electrical info	
ELECTRICAL	100-240V / 50-60Hz
CLASS	II
POWER SUPPLY	YES
DIM TYPE	non-dimmable
ENERGY CLASS	D
CERTIFICATES	CB, ENEC, RCM

Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 5,8W / CRI>90 (R9: 52) / 3000K / 787lm
TM-30 VALUES	Rf: 90 / Rg: 99
SDCM	SDCM1
RISKGROUP	RG1
LM80	L90B10 > 50000
LED TECHNICS (LIGHT SOURCE)	787lm // 5,8W // 135lm/W
LED TECHNICS (LUMINAIRE)	735lm // 7W // 110lm/W

For detailed installation instructions, please consult the manual: [279\\_61\\_811\\_XXX\\_HAND.pdf](#)



**ULTRA X LED 930 A**

279 61 811 930 A

Notes: