



ULTRA X DOWN-UP LED 930 N



279 61 812 930 N

AVAILABLE IN

ALU GREY 279 61 812 930 A

ANTHRACITE (DARK GREY) 279 61 812 930 N

WHITE 279 61 812 930 W



[View on website](#)

General info

LOCATION	indoor-outdoor
INSTALLATION	Wall Surface mounted
INGRESS PROTECTION	IP55
PROTECTION AGAINST MECHANICAL IMPACT	IK03
WEIGHT (KG)	0.9
ADJUSTABILITY	non adjustable
INFORMATION	INCL.2 x LENS INCL.DIMMABLE LED POWER SUPPLY 350mA-DC

Electrical info

ELECTRICAL	220-240V / 50-60Hz
CLASS	I
POWER SUPPLY	YES
DIM TYPE	mains (phase cut-off)
ENERGY CLASS	D

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	2 x (LED array 5,8W / CRI>90 (R9: 52) / 3000K / 787lm)
TM-30 VALUES	rf: 90 / Rg: 99
SDCM	SDCM1
RISKGROUP	RG1
LM80	L90B10 > 50000
LED TECHNICS (LIGHT SOURCE)	1574lm // 11,6W // 135lm/W
LED TECHNICS (LUMINAIRE)	1469lm // 13W // 110lm/W

For detailed installation instructions, please consult the manual: [279_61_812_XXX_HAND.pdf](#)



ULTRA X DOWN-UP LED 930 N

279 61 812 930 N

Notes: