





## MICROSPY 39 C 92745 B

279 773 811 921 B

AVAILABLE IN

**BLACK** 279 773 811 921 B

**WHITE** 279 773 811 921 W



[View on website](#)



### General info

<b>LOCATION</b>	indoor
<b>INSTALLATION</b>	Ceiling Suspended
<b>INGRESS PROTECTION</b>	IP20
<b>WEIGHT (KG)</b>	0.7
<b>ADJUSTABILITY</b>	non adjustable
<b>INFORMATION</b>	REFLECTOR WFL-45° INCL.LED POWER SUPPLY 350mA-DC INCL.1 x CABLE 2 x 0.75mm <sup>2</sup> / 1,6m

### Electrical info

<b>ELECTRICAL</b>	110-240V / 50-60Hz
<b>CLASS</b>	II
<b>POWER SUPPLY</b>	YES
<b>DIM TYPE</b>	non-dimmable
<b>ENERGY CLASS</b>	D

### Lightsource info

<b>LIGHTSOURCE NAME</b>	LED
<b>LIGHTSOURCE</b>	LED array 5,8W / CRI>90 (R9: 60) / 2700K / 753lm
<b>TM-30 VALUES</b>	rf: 89 / Rg: 100
<b>SDCM</b>	SDCM1
<b>RISKGROUPE</b>	RG1
<b>LM80</b>	L90B10 > 50000
<b>LED TECHNICS (LIGHT SOURCE)</b>	753lm // 5,8W // 129lm/W
<b>LED TECHNICS (LUMINAIRE)</b>	507lm // 7W // 76lm/W

### Options

CONNECTION TRIMLESS


For detailed installation instructions, please consult the manual: [279\\_773\\_811\\_XXX\\_HAND.pdf](#)

MICROSPY 39 C 92745 B

279 773 811 921 B

FINISH YOUR SPECIFICATION

Suspension parts



Technical drawing of Cable Clamp B. Dimensions: 28 (length), 81 (width), 59 (height).

**15229 0010 B** CABLE CLAMP B

☐

Electric connection parts



Technical drawing of Connection Trimless O.F.A. Dimensions: 150 (length), 100 (width), 75 (height), Ø25 (hole diameter).

**328 10 03** CONNECTION TRIMLESS O.F.A.

☐

Notes: