





MULTINOVA 355 PRISM 930 DIM4 B  
28063 9304 B

AVAILABLE IN  
**BLACK** 28063 9304 B  
**WHITE** 28063 9304 W



 [View on website](#)

General info	
LOCATION	indoor
INSTALLATION	Ceiling Suspended
INGRESS PROTECTION	IP20
WEIGHT (KG)	14
ADJUSTABILITY	non adjustable
INFORMATION	INCL.PC PRISMATIC INCL.DIMMABLE LED POWER SUPPLY INCL.3 x CABLE SUSPENSION SINGLE AUTO. 3.0m INCL.1 x CABLE 5 x 0.75mm <sup>2</sup>

Electrical info	
ELECTRICAL	220-240V / 50-60Hz
CLASS	I
POWER SUPPLY	YES
DIM TYPE	DALI or DSI or push button
ENERGY CLASS	D
CERTIFICATES	CB, ENEC, RCM

Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	3 x (LED cluster 34,4W / CRI>90 (R9: 68) / 3000K / 4767lm)
TM-30 VALUES	Rf: 89 / Rg: 97
SDCM	SDCM3
LM80	L70 > 60000
LED TECHNICS (LIGHT SOURCE)	14301lm // 103,2W // 139lm/W
LED TECHNICS (LUMINAIRE)	10398lm // 119W // 88lm/W

Options	
CABLE BASE R / S	
COVERSET R 62-90-100	
CONNECTION ST / CONNECTION TRIMLESS	
SUSPENSION ST / SUSPENSION TRIMLESS	



## **MULTINOVA 355 PRISM 930 DIM4 B**

28063 9304 B


For detailed installation instructions, please consult the manual: [28063\\_XXX4\\_HAND.pdf](#)

MULTINOVA 355 PRISM 930 DIM4 B

28063 9304 B

FINISH YOUR SPECIFICATION

Current supply




41 **203 99 55 ANO** CABLE BASE R ANO

☐

**203 99 55 B** CABLE BASE R B

☐

**203 99 55 W** CABLE BASE R W

☐

41 **203 99 56 ANO** CABLE BASE S ANO

☐


**203 99 56 B** CABLE BASE S B

☐

**203 99 56 W** CABLE BASE S W

☐

Coversets



**204 00 100 B** COVERSET R 100 B

☐

**204 00 100 W** COVERSET R 100 W

☐

MULTINOVA 355 PRISM 930 DIM4 B

28063 9304 B

Suspension parts



**328 10 01**

SUSPENSION TRIMLESS O.F.A.

☐



**15225 0340 B**

SUSPENSION ST B

☐

**15225 0340 W**

SUSPENSION ST W

☐

Electric connection parts



**328 10 03**

CONNECTION TRIMLESS O.F.A.

☐



**15225 0360 B**

CONNECTION ST B

☐

**15225 0360 W**

CONNECTION ST W

☐

Notes: