





SPYCO ON 3 AC 92733 DIM8 B
28316 9228 B

AVAILABLE IN
BLACK 28316 9228 B
WHITE 28316 9228 W



 [View on website](#)

General info

LOCATION	indoor
INSTALLATION	Ceiling Surface mounted
INGRESS PROTECTION	IP20
WEIGHT (KG)	1.1
ADJUSTABILITY	0° to 90° swiveling, 350° rotatable
INFORMATION	REFLECTOR FL-33° BLACK version: INCL.SPY TUBE S B / WHITE version: INCL.SPY TUBE S W

Electrical info

ELECTRICAL	230V / 50-60Hz
CLASS	I
DIM TYPE	mains (phase cut-off)
ENERGY CLASS	F

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	3 x (AC LED array 8W / CRI>90 (R9: 55) / 2700K / 597lm)
TM-30 VALUES	Rf: 92 / Rg: 98
SDCM	SDCM3
RISKGROUP	RG1
LM80	L80B10 > 67000
LED TECHNICS (LIGHT SOURCE)	1791lm // 24W // 75lm/W
LED TECHNICS (LUMINAIRE)	1357lm // 24W // 57lm/W

Accessories

SPY TUBE S


For detailed installation instructions, please consult the manual: [28316_XXX8_HAND.pdf](#)

SPYCO ON 3 AC 92733 DIM8 B

28316 9228 B

FINISH YOUR SPECIFICATION

Finish your product



414 02 00 B

SPY TUBE S B

☐

414 02 00 MMAT

SPY TUBE S MMAT

☐

414 02 00 W

SPY TUBE S W

☐

Notes: